

INSTRUCTIONS LUNAR LANDER

FOR TRS-80 MODEL 1 & MODEL 3

BY JACK MONCRIEF & MIKE WALL

APPROXIMATELY 70 HOURS INTO YOUR APOLLO MISSION, YOU'RE SEATED SECURELY IN YOUR LEM, DROPPING SOFTLY TOWARDS ONE OF THE MANY LANDING SITES BELOW. SUDDENLY, YOUR PANEL LIGHTS INDICATE THAT THE ON-BOARD RADAR IS MALFUNCTIONING - - - YOU'VE LOST READOUTS FOR ALTITUDE AND SPEEDS. BEYOND THE POINT TO ABORT THE MISSION, YOU ARE FORCED TO ATTEMPT A LANDING USING ONLY VISUAL REFERENCES. YOUR BEST CHANCE IS TO WATCH THE VIDEO DISPLAY AS HOUSTON'S "MISSION CONTROL" FOLLOWS YOUR DESCENT USING A TELEVISION CAMERA LEFT ON THE MOON BY THE LAST MISSION.

AS THE LETTERS FROM THE LAST MESSAGE DISAPPEAR FROM THE SCREEN, THE IMAGE OF YOUR CRAFT DRIFTING ACROSS THE JAGGED, LUNAR HORIZON COMES INTO VIEW. ALTHOUGH THE MOON'S GRAVITY IS A FRACTION OF EARTH'S, THE MAIN ENGINES WORK SLUGGISHLY TO OVERCOME IT (HOLDING THE -SPACE BAR- DOWN CONTINUES THE THRUST). SMALL DIRECTIONAL ROCKETS CONTROL YOUR LATERAL MOVEMENT (AGAIN HOLDING EITHER ARROW KEY DOWN CAUSES THE ENGINE TO CONTINUE TO "BURN"). SUCCESSFUL LANDINGS EARN POINTS CORRESPONDING TO THE VALUES BELOW THE SITES WHILE A CRASH DEDUCTS A THOUSAND UNITS OF FUEL. NOTE THE DEEP RAVINE WHERE YOU CAN ALSO REFUEL UP TO 3 TIMES!

WITH EXCELLENT ANIMATION AND REALISTIC SOUND, THIS PROGRAM WILL MAKE "LUNATICS" OF ALL OF US!

SEE OTHER SIDE FOR SOUND AND LOADING INSTRUCTIONS

ai  **Adventure**
INTERNATIONAL
A DIVISION OF SCOTT ADAMS, INC.

**BOX 3435
LONGWOOD,
FLA. 32750
(305) 862-6917**

LUNAR LANDER

LOADING INSTRUCTIONS FOR TRS-80

TO LOAD LUNAR LANDER FROM TAPE

- 1) IF MODEL 1, SHUT OFF EXPANSION INTERFACE.
- 2) IF MODEL 3, SELECT LOW CASSETTE SPEED
- 3) TYPE: SYSTEM
- 4) TYPE: LUNAR
- 5) TAPE SHOULD LOAD WITH TWO BLINKING * IN UPPER CORNER. IF A "C" SHOWS UP, REBOOT SYSTEM AND RETURN TO STEP #3.
- 6) TYPE: /

TO LOAD LUNAR LANDER FROM DISK -
PUT IN DRIVE 0 AND BOOT SYSTEM.

HOW TO OUTPUT SOUND ON YOUR TRS-80

- 1) Load sound program into computer.
- 2) Plug mike wire from computer into "Aux" on cassette player. (This is its normal position.)
- 3) Remove remote plug.
- 4) Plug in earphone or any speaker (up to Hi-Fi size) into the earphone jack on the cassette recorder.
- 5) Open the cassette recorder top as if you were putting tape in. In the left back you will see a small micro switch. If you press this switch you will be able to press the "record" switch down. Do this now.
- 6) Press the "record" switch and the "play" switch at the same time.
- 7) You should now get sound from your earphone or your speaker.

ai



Copyright 1980
Adventure
INTERNATIONAL

A DIVISION OF SCOTT ADAMS, INC.

BOX 3435
LONGWOOD,
FLA. 32750
(305) 862-6917