

TRS-80[®] MODEL 4

Computer Graphics

**Catalog
Number
26-1126**

Radio Shack

TRS-80

SOFTWARE

CUSTOM MANUFACTURED IN USA BY RADIO SHACK, A DIVISION OF TANDY CORP.

TERMS AND CONDITIONS OF SALE AND LICENSE OF RADIO SHACK COMPUTER EQUIPMENT AND SOFTWARE
PURCHASED FROM A RADIO SHACK COMPANY-OWNED COMPUTER CENTER, RETAIL STORE OR FROM A
RADIO SHACK FRANCHISEE OR DEALER AT ITS AUTHORIZED LOCATION

LIMITED WARRANTY

I. CUSTOMER OBLIGATIONS

- A. CUSTOMER assumes full responsibility that this Radio Shack computer hardware purchased (the "Equipment"), and any copies of Radio Shack software included with the Equipment or licensed separately (the "Software") meets the specifications, capacity, capabilities, versatility, and other requirements of CUSTOMER.
- B. CUSTOMER assumes full responsibility for the condition and effectiveness of the operating environment in which the Equipment and Software are to function, and for its installation.

II. RADIO SHACK LIMITED WARRANTIES AND CONDITIONS OF SALE

- A. For a period of ninety (90) calendar days from the date of the Radio Shack sales document received upon purchase of the Equipment, RADIO SHACK warrants to the original CUSTOMER that the Equipment and the medium upon which the Software is stored is free from manufacturing defects. THIS WARRANTY IS ONLY APPLICABLE TO PURCHASES OF RADIO SHACK EQUIPMENT BY THE ORIGINAL CUSTOMER FROM RADIO SHACK COMPANY-OWNED COMPUTER CENTERS, RETAIL STORES AND FROM RADIO SHACK FRANCHISEES AND DEALERS AT ITS AUTHORIZED LOCATION. The warranty is void if the Equipment's case or cabinet has been opened, or if the Equipment or Software has been subjected to improper or abnormal use. If a manufacturing defect is discovered during the stated warranty period, the defective Equipment must be returned to a Radio Shack Computer Center, a Radio Shack retail store, participating Radio Shack franchisee or Radio Shack dealer for repair, along with a copy of the sales document or lease agreement. The original CUSTOMER'S sole and exclusive remedy in the event of a defect is limited to the correction of the defect by repair, replacement, or refund of the purchase price, at RADIO SHACK'S election and sole expense. RADIO SHACK has no obligation to replace or repair expendable items.
- B. RADIO SHACK makes no warranty as to the design, capability, capacity, or suitability for use of the Software, except as provided in this paragraph. Software is licensed on an "AS IS" basis, without warranty. The original CUSTOMER'S exclusive remedy, in the event of a Software manufacturing defect, is its repair or replacement within thirty (30) calendar days of the date of the Radio Shack sales document received upon license of the Software. The defective Software shall be returned to a Radio Shack Computer Center, a Radio Shack retail store, participating Radio Shack franchisee or Radio Shack dealer along with the sales document.
- C. Except as provided herein no employee, agent, franchisee, dealer or other person is authorized to give any warranties of any nature on behalf of RADIO SHACK.
- D. Except as provided herein, **RADIO SHACK MAKES NO WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.**
- E. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation(s) may not apply to CUSTOMER.

III. LIMITATION OF LIABILITY

- A. EXCEPT AS PROVIDED HEREIN, RADIO SHACK SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO CUSTOMER OR ANY OTHER PERSON OR ENTITY WITH RESPECT TO ANY LIABILITY, LOSS OR DAMAGE CAUSED OR ALLEGED TO BE CAUSED DIRECTLY OR INDIRECTLY BY "EQUIPMENT" OR "SOFTWARE" SOLD, LEASED, LICENSED OR FURNISHED BY RADIO SHACK, INCLUDING, BUT NOT LIMITED TO, ANY INTERRUPTION OF SERVICE, LOSS OF BUSINESS OR ANTICIPATORY PROFITS OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OR OPERATION OF THE "EQUIPMENT" OR "SOFTWARE". IN NO EVENT SHALL RADIO SHACK BE LIABLE FOR LOSS OF PROFITS, OR ANY INDIRECT, SPECIAL, OR CONSEQUENTIAL DAMAGES ARISING OUT OF ANY BREACH OF THIS WARRANTY OR IN ANY MANNER ARISING OUT OF OR CONNECTED WITH THE SALE, LEASE, LICENSE, USE OR ANTICIPATED USE OF THE "EQUIPMENT" OR "SOFTWARE".
NOTWITHSTANDING THE ABOVE LIMITATIONS AND WARRANTIES, RADIO SHACK'S LIABILITY HEREUNDER FOR DAMAGES INCURRED BY CUSTOMER OR OTHERS SHALL NOT EXCEED THE AMOUNT PAID BY CUSTOMER FOR THE PARTICULAR "EQUIPMENT" OR "SOFTWARE" INVOLVED.
- B. RADIO SHACK shall not be liable for any damages caused by delay in delivering or furnishing Equipment and/or Software.
- C. No action arising out of any claimed breach of this Warranty or transactions under this Warranty may be brought more than two (2) years after the cause of action has accrued or more than four (4) years after the date of the Radio Shack sales document for the Equipment or Software, whichever first occurs.
- D. Some states do not allow the limitation or exclusion of incidental or consequential damages, so the above limitation(s) or exclusion(s) may not apply to CUSTOMER.

IV. RADIO SHACK SOFTWARE LICENSE

RADIO SHACK grants to CUSTOMER a non-exclusive, paid-up license to use the RADIO SHACK Software on **one** computer, subject to the following provisions:

- A. Except as otherwise provided in this Software License, applicable copyright laws shall apply to the Software.
- B. Title to the medium on which the Software is recorded (cassette and/or diskette) or stored (ROM) is transferred to CUSTOMER, but not title to the Software.
- C. CUSTOMER may use Software on one host computer and access that Software through one or more terminals if the Software permits this function.
- D. CUSTOMER shall not use, make, manufacture, or reproduce copies of Software except for use on **one** computer and as is specifically provided in this Software License. Customer is expressly prohibited from disassembling the Software.
- E. CUSTOMER is permitted to make additional copies of the Software **only** for backup or archival purposes or if additional copies are required in the operation of **one** computer with the Software, but only to the extent the Software allows a backup copy to be made. However, for TRSDOS Software, CUSTOMER is permitted to make a limited number of additional copies for CUSTOMER'S own use.
- F. CUSTOMER may resell or distribute unmodified copies of the Software provided CUSTOMER has purchased one copy of the Software for each one sold or distributed. The provisions of this Software License shall also be applicable to third parties receiving copies of the Software from CUSTOMER.
- G. All copyright notices shall be retained on all copies of the Software.

V. APPLICABILITY OF WARRANTY

- A. The terms and conditions of this Warranty are applicable as between RADIO SHACK and CUSTOMER to either a sale of the Equipment and/or Software License to CUSTOMER or to a transaction whereby RADIO SHACK sells or conveys such Equipment to a third party for lease to CUSTOMER.
- B. The limitations of liability and Warranty provisions herein shall inure to the benefit of RADIO SHACK, the author, owner and/or licensor of the Software and any manufacturer of the Equipment sold by RADIO SHACK.

VI. STATE LAW RIGHTS

The warranties granted herein give the **original** CUSTOMER specific legal rights, and the **original** CUSTOMER may have other rights which vary from state to state.

TRS-80® Computer Graphics Operation Manual: Copyright 1983, All Rights Reserved, Tandy Corporation.

Reproduction or use without express written permission from Tandy Corporation, of any portion of this manual is prohibited. While reasonable efforts have been taken in the preparation of this manual to assure its accuracy, Tandy Corporation assumes no liability resulting from any errors or omissions in this manual, or from the use of the information obtained herein.

TRSDOS 6 Copyright 1983 Logical Systems, Inc. All Rights Reserved, Licensed to Tandy Corporation.

BASIC Software Copyright 1983, Microsoft, Inc., All Rights Reserved, Licensed to Tandy Corporation.

BASICG Software Copyright 1983, Microsoft, Inc., All Rights Reserved, Licensed to Tandy Corporation.

Contents

To Our Customers	4
1/ Computer Graphics Overview	7
2/ Graphics BASIC (BASICG).....	11
BASICG Commands	11
Starting-Up	12
3/ Graphics Utilities	45
4/ Graphics Subroutine Library (FORTRAN).....	69
5/ Programming the Graphics Board	85
Appendix A/ BASICG/Utilities Reference Summary	87
Appendix B/ BASICG Error Codes and Messages	89
Appendix C/ Subroutine Language Reference Summary.....	95
Appendix D/ Sample Programs	97
BASICG	97
Printing Graphics Displays	103
FORTTRAN Sample Programs.....	104
Appendix E/ Base Conversion Chart	119
Appendix F/ Pixel Grid Reference	123
Appendix G/ Line Style Reference	129
Index	131

Model 4 Computer Graphics

To Our Customers . . .

The TRS-80® Computer Graphics package revolutionizes your Model 4 by letting you draw intricate displays from simple program instructions. With the highly defined Graphics Screen, the list of practical applications is nearly endless!

The TRS-80 Computer Graphics package includes a:

- Computer Graphics Diskette
- Computer Graphics Operation Manual

However, before you can use this package, your Model 4 must have 64K of RAM (Random Access Memory) and one disk drive. Your computer must also be modified by a qualified Radio Shack service technician.

Included on the Graphics diskette are:

- TRSDOS Version 6
- Graphics BASIC (BASICG)
- Graphics Subroutine Library (GRPLIB)
- Graphics Utilities
- Sample Programs in BASICG and FORTRAN

To print graphic displays, you can use any Radio Shack printer that has graphic capabilities such as Line Printer VII (26-1167), Line Printer VIII (26-1168), DMP-100 (26-1253), DMP-200 (26-1254), DMP-400 (26-1251), or DMP-500 (26-1252).

You can also utilize the Graphics Subroutine Library with several languages, including, but not limited to, FORTRAN (26-2219).

About This Manual . . .

For your convenience, we've divided this manual into five sections plus appendices:

- Computer Graphics Overview
- Graphics BASIC (BASICG) Language Description
- Graphics Utilities
- FORTRAN Description
- Programming the Graphics Board
- Appendices

This package contains two separate (but similar) methods for Graphics programming:

- Graphics BASIC (BASICG)
- Graphics Subroutine Library

If you're familiar with Model 4 TRSDOS™ and BASIC, you should have little trouble in adapting to Graphics BASIC. If you want to review BASIC statements and syntax, see your *Model 4 Disk System Owner's Manual*. Then read Chapters 1, 2 and 3, along with Appendixes A, B, D, and E of this manual.

If it's Graphics applications in FORTRAN you're after, refer to the TRS-80 FORTRAN manual. Then read Chapters 1, 2, 3, and 4 as well as Appendixes C, D, E, and F of this manual.

Note: This manual is written as a reference manual for the TRS-80 Computer Graphics package. It is not intended as a teaching guide for graphics programming.

Notational Conventions

The following conventions are used to show syntax in this manual:

CAPITALS	Any words or characters which are uppercase must be typed in exactly as they appear.
<i>lowercase italics</i>	Fields shown in lowercase italics are variable information that you must substitute a value for.
(ENTER)	Any word or character contained within a box represents a keyboard key to be pressed.
...	Ellipses indicate that a field entry may be repeated.
<i>filespec</i>	A field shown as filespec indicates a standard TRSDOS file specification of the form: <i>filename/ext.password:d</i>
punctuation	Punctuation other than ellipses must be entered as shown.
delimiters	Commands must be separated from their operands by one or more blank spaces. Multiple operands, where allowed, may be separated from each other by a comma, a comma followed by one or more blanks, or by one or more blanks. Blanks and commas may not appear within an operand.

1/ Computer Graphics Overview

Graphics is the presentation of dimensional artwork. With TRS-80 Computer Graphics, the artwork is displayed on a two-dimensional plane — your computer screen. Like an artist's easel or a teacher's blackboard, the screen is a "drawing board" for your displays.

TRS-80 Computer Graphics has two colors:

- Black (OFF)
- White (ON)

Graphics programming is different from other types of programming because your ultimate result is a pictorial display (bar graph, pie chart, etc.) rather than textual display (sum, equation, etc.). This is an important distinction. After working with graphics for a while, you'll find yourself thinking "visually" as you write programs.

In computer-generated graphics, displays can include tables, charts, graphs, illustrations and other types of artwork. Once they're created, you can "paint" displays with a variety of styles and shapes, or even simulate animation.

The Computer Graphics program uses a "high-resolution" screen. The more addressable points or dots (called "pixels") on a computer's screen, the higher the resolution. A lower resolution screen has fewer addressable pixels.




Figure 1. Resolution

Since the TRS-80 has high-resolution — 640 pixels on the X-axis (0 to 639) and 240 pixels on the Y-axis (0 to 239) — you can draw displays that have excellent clarity and detail.

How TRS-80 Computer Graphics Works

The concept of graphics is fairly simple. Each point on the screen can be turned ON (white) or OFF (black).

When you clear the Graphics Screen, all graphic points are turned OFF.

Therefore, by setting various combinations of the pixels (usually with a single command) either ON or OFF, you can generate lines, circles, geometric figures, pictures, etc.

Model 4 Computer Graphics

The Graphics Screen

TRS-80 Computer Graphics has two “screens” — Text and Graphics. (We’ll call them screens, although they are really modes.) Both screens can act independently of each other and make use of the computer’s entire display area.

The Text Screen, also referred to as the “Video Display,” is the “normal” screen where you type in your programs. The Graphics Screen is where graphic results are displayed. Both screens can be cleared independently. Note: The Graphics Screen will not automatically be cleared when you return to TRSDOS. It will be cleared when you re-enter BASICG.

The Graphics Screen cannot be displayed at the same time as the Text Screen.

While working with Computer Graphics, it might be helpful to imagine the screen as a large Cartesian coordinate plane (with a horizontal X- and a vertical Y-axis). However, unlike some coordinate systems, TRS-80 Computer Graphics’ coordinate numbering starts in the upper-left corner — (0,0) — and increases toward the lower-right corner — (639,239). The lower-left corner is (0,239) and the upper-right corner is (639,0).

Since the screen is divided into X-Y coordinates (like the Cartesian system), each pixel is defined as a unique position. In TRS-80 Computer Graphics, you can directly reference these coordinates as you draw.

About Ranges...

Some TRS-80 Computer Graphics commands accept values within the Model 4 integer range (– 32768 to 32767), instead of just 0 to 639 for X and 0 to 239 for Y. Since most of the points in the integer range are off the screen, these points are part of what is called Graphics “imaginary” Cartesian system.




Figure 2. Graphics Visible Screen

Computer Graphics Overview




Figure 3. Graphics “Imaginary” Cartesian System

2/ Graphics BASIC

Graphics BASIC (BASICG) vs. BASIC

The Graphics BASIC file on the supplied diskette is named BASICG.

You can load and run a BASIC file from either BASICG or BASIC. You cannot run programs that contain BASICG statements while in BASIC.

Important Note: Because of memory limitations, some programs (i.e., some application programs) will not run in BASICG. BASICG uses approximately 6.6K more memory than BASIC. Some Graphics Commands use Free Memory. This means that the larger your BASIC programs are, the more limitations on your Graphics capabilities.

Each Graphics program statement has a specific syntax and incorporates a Graphics BASIC command or function.

Table 1 gives a brief description of the BASICG commands; Table 2 lists the BASICG functions. This section of the manual will describe each statement and function in detail.

BASICG Commands	
Command	Description
CIRCLE	Draws a circle, arc, semicircle, etc.
CLR	Clears the Graphics Screen.
GLOCATE	Sets the Graphics Cursor and the direction for putting characters on the Graphics Screen.
GET	Reads the contents of a rectangle on the Graphics Screen into an array for future use by PUT.
LINE	Draws a line from the startpoint to the endpoint in the specified line style and color. Also creates a box.
PAINT	Paints an area, starting from a specified point. Also paints a specified style.
PRESET	Sets an individual dot (pixel) OFF (or ON).
PRINT #-3	Writes characters to the Graphics Screen.
PSET	Sets an individual dot (pixel) ON (or OFF).
PUT	Stores graphics from an array onto the Graphics Screen.
SCREEN	Selects the Graphics or Text Screen.
VIEW	Creates a viewport which becomes the current Graphics Screen.

Table 1

Model 4 Computer Graphics

BASICG Functions	
Function	Description
&POINT	Returns the OFF/ON color value of a pixel.
&VIEW	Returns the current viewport coordinates.

Table 2

Starting-Up

Before using the diskette included with this package, be sure to make a "safe copy" of it. See your *Model 4 Introduction to Your Disk System* for information on BACKUP.

To load BASICG:

1. Power up your System according to the start-up procedure in your *Model 4 Introduction to Your Disk System*.
2. Insert the backup diskette into Drive 0.
3. Initialize the System as described in your *Model 4 Introduction to Your Disk System*.
4. When TRSDOS Ready appears, type:

BASICG (ENTER)

The Graphics BASIC start-up prompts, followed by the READY prompt appear, and you are in Graphics BASIC. You can now begin BASICG programming.

Remember that Model 4 numeric values are as follows:

Model 4 Numeric Values			
Numeric Type	Range	Storage Requirement	Example
Integer	- 32768, 32767	2 bytes	240, 639, - 10
Single-Precision	- 1×10^{38} , - 1×10^{-38} + 1×10^{38} , + 1×10^{-38} Up to 7 significant digits (Prints six)	4 bytes	22.50, 3.14259 - 100.001
Double-Precision	- 1×10^{38} , - 1×10^{-38} + 1×10^{38} , + 1×10^{-38} Up to 17 significant digits (Prints 16)	8 bytes	1230000.00 3.1415926535897932

Table 3

Graphics BASIC (BASICG)

With each BASICG command or function, there are various options which you may or may not include in a program statement (depending on your needs). Each option is separated from the previous option by a delimiter, usually a comma. When you do not specify an available option (e.g., you use the default value) and you specify subsequent options, you must still enter the delimiter or a Syntax Error will result. (See your *Model 4 Disk System Owner's Manual* for more information.)

Because you are dealing with two distinct screens, the Graphics Screen and the Text Screen, we strongly urge you to read the description of the **SCREEN** command before continuing.

CIRCLE

Draws Circle, Semicircle, Ellipse, Arc, Point

CIRCLE (x,y),r,c,start,end,ar

(x,y) specifies the centerpoint of the figure. **x** and **y** are integer expressions.

r specifies the radius of the figure in pixels and is an integer expression.

c specifies the OFF/ON color of the figure and is an integer expression of either 0 (OFF/black) or 1 (ON/white). **c** is optional; if omitted, 1 is used.

start specifies the startpoint of the figure and is a numeric expression from 0 to 6.283185. **start** is optional; if omitted, 0 is used.

end specifies the endpoint of the figure and is a numeric expression from 0 to 6.283185. **end** is optional; if omitted, 6.283185 is used.

ar specifies the aspect ratio of the circle, is a single-precision floating-point number > 0.0 (to 1×10^{38}) and determines the major axis of the figure. **ar** is optional; if omitted, .5 is used and a circle is drawn.

The CIRCLE command lets you draw five types of figures:




Figure 4. Types of Displays with CIRCLE

With CIRCLE, you can enter values for PI (and $2 \times \text{PI}$) up to 37 significant digits without getting an overflow error. However, only 16 digits are displayed.

3.1415926535897932384626433832795028841
6.2831853071795864769252867665590057682

Model 4 Computer Graphics

However, you'll probably only be able to visually detect a change in the circle's *start* and *end* when PI is accurate to a few significant digits (e.g., 3.1, 6.28, etc.). The *start* and *end* values can't be more than $2 \times \text{PI}$ (e.g., 6.2832 will not work) or an Illegal Function Call error will occur.

(x,y)

Centerpoint

The (x,y) coordinates in the CIRCLE statement specify the centerpoint of the figure. x and y are numeric expressions in the integer number range.

Example

```
CIRCLE (x,y),r  
CIRCLE (320,120),r
```




Figure 5. Center of Circle

r

Radius

The radius of a circle is measured in pixels and is a numeric expression in the integer range. Radius is the distance from the centerpoint to the edge of the figure. Although a negative value will be accepted by BASICG, the results of using a negative value are unpredictable.

The radius is either on the X-axis or Y-axis, depending on the aspect ratio (see *ar*). If the aspect ratio is greater than 1, the radius is measured on the Y-axis. If the aspect ratio is less than or equal to 1, the radius is measured on the X-axis.

Example

```
10 CIRCLE(320,120),100
```

This example draws a circle. The radius is 100 and the centerpoint is (320,120).

c

Color

You can get the ON/OFF (white/black) color of a figure's border and radius lines (see *chart/end*) by specifying a numeric value of 1 or 0.

If you omit color, BASICG uses 1 (ON/white).




Figure 6. Border of Circle

start/end

Startpoint/Endpoint of Circle

The range for *start* and *end* is 0 to 6.283185 ($2 \times \pi$).

If you do not enter *start* and *end*, the default values of 0 and 6.28, respectively, are used.

A negative *start* or *end* value will cause the respective radius to be drawn in addition to the arc (i.e., it will draw a "piece of the pie"). The actual start and endpoints are determined by taking the absolute value of the specified start and endpoints. These values are measured in radians.

Note: Radius will not be drawn if *start* or *end* is -0 . To draw a radius with *start* or *end* as 0, you must use $-0.000...01$.




Figure 7. Clock/Radian Equivalents

Model 4 Computer Graphics

Degrees	Radians	Clock Equivalent
0	0	3:00
90	1.57	12:00
180	3.14	9:00
270	4.71	6:00
360	6.28	3:00

Table 4. Degree/Radians/Clock Equivalents

You can draw semicircles and arcs by varying *start* and *end*. If *start* and *end* are the same, a point (one pixel) will be displayed instead of a circle.




Figure 8. CIRCLE's (-) start, (-) end

You can have a positive *start* and a negative *end* (or vice versa) as well as negative *starts* and *ends*. In these cases, only one radius line is drawn.




Figure 9. CIRCLE's (+) start, (-) end

Hints and Tips about *start* and *end*:

- When using the default values for *start* and *end*, you must use commas as delimiters if you wish to add more parameters.
- If you use *PI*, it is not a reserved word in BASICG and must be defined in your program.

ar

Aspect Ratio

You can draw ellipses by varying the aspect ratio from the default value (.5) for a circle (and semicircle).

Every ellipse has a “major axis” which is the ellipse’s longer, predominant axis. With an ellipse (as with a circle), the two axes are at right angles to each other.

The mathematical equation for determining the aspect ratio is:

$$ar = \text{length of Y-axis} / \text{length of X-axis}$$

- If the aspect ratio is .5, a circle is drawn.
- If the ratio is less than .5, an ellipse with a major axis on the X-axis is drawn.
- If the ratio is greater than .5, an ellipse with a major axis on the Y-axis is drawn.




Figure 10. CIRCLE's Ellipse

The range for aspect ratio is a single-precision floating-point number greater than 0.0 (to 1×10^{38}). Although a negative value will be accepted by BASICG, the results of using a negative value are unpredictable.

Hints and Tips about *aspect ratio*:

- Entering .5 as the ratio produces a circle.
- Numbers between 0 and .5 produce an ellipse with a major axis on X.
- Numbers over .5 generate an ellipse with a major axis on Y.
- Even though you can enter large aspect ratios, large numbers may produce straight lines.

Model 4 Computer Graphics

Examples

```
CIRCLE (320,120),90,1
```

This example draws a white-bordered circle with the centerpoint of (320,120) and radius of 90.

```
CIRCLE (320,120),90,1,,,7
```

This statement draws a white-bordered ellipse with an origin of (320,120) and radius of 90. The major axis is the Y-axis.

```
CIRCLE (320,120),90,1,-6.2,-5
```

This statement draws an arc with a vertex ("origin") of (320,120) and radius of 90. *start* is 6.2 and *end* is 5. Radius lines are drawn for *start* and *end*.

```
CIRCLE (320,120),90,1,-,4
```

This example draws an arc with a vertex of (320,120) and radius of 90. *start* is 0 and *end* is 4. A radius line is drawn for *end*.

```
10 PI=3.1415926
```

```
20 CIRCLE (320,120),100,1,PI,2*PI,,5
```

A semicircle is drawn.

```
10 CIRCLE (150,100),100,1,-5,-1
```

```
20 CIRCLE (220,100),100,1,5,1
```

Two arcs are drawn with the same *start* and *end* point. The arc with the negative *start* and *end* has two radius lines drawn to the vertex. The arc with a positive *start* and *end* has no radius lines.

```
CIRCLE (320,120),140,-,4,6.1
```

This statement draws an arc with a vertex at (320,120) and a radius of 140. *Start* is 4 and *end* is 6.1. A radius line is drawn for *start*.

```
CIRCLE (320,120),140,1,0,1,,5
```

This example draws an arc with a vertex of (320,120) and radius of 140.

Sample Program

```
4 SCREEN 0
5 CLR
10 FOR X =10 TO 200 STEP 10
20 CIRCLE (300,100),X,1,,,9
30 NEXT X
40 FOR Y=10 TO 200 STEP 10
50 CIRCLE (300,100),Y,1,,,1
60 NEXT Y
70 FOR Z=10 TO 200 STEP 10
80 CIRCLE (300,100),Z,1,,,5
90 NEXT Z
100 GOTO 5
```

Graphics BASIC (BASICG)

A set of 20 concentric ellipses is drawn with a major axis on Y, a set of 20 concentric ellipses is drawn with a major axis on X, and a set of 20 concentric circles is drawn. The ellipses and circles in each of the three groups are concentric and the radius varies from 10 to 200.

CLR

Clears the Graphics Screen

CLR

CLR clears the Graphics Screen.

Example

```
10 SCREEN 0
20 CIRCLE(320,120),100,1
```

This program line will draw a circle. Now type:

```
CLR (ENTER)
```

and the Graphics Screen will be cleared but the Text Screen will remain unchanged. This can be seen by typing:

```
SCREEN 1
```

GET

Reads the Contents of Rectangular Pixel Area into Array

GET(x1,y1)-(x2,y2),array name

(x1,y1) are coordinates of one of the opposing corners of a rectangular pixel area. *x1* is an integer expression from 0 to 639. *y1* is an integer expression from 0 to 239.

(x2,y2) are coordinates of the other corner of a rectangular pixel area. *x2* is an integer expression from 0 to 639. *y2* is an integer expression from 0 to 239.

array name is the name you assign to the array that will store the rectangular area's contents. *array name* must be specified.

Important Note: BASICG recognizes two syntaxes of the command GET — the syntax described in this manual and the syntax described in the *Model 4 Disk System Owner's Manual*. BASIC recognizes only the GET syntax described in the *Model 4 Disk System Owner's Manual*.

GET reads the graphic contents of a rectangular pixel area into a storage array for future use by PUT (see PUT).

A rectangular pixel area is a group of pixels which are defined by the diagonal line coordinates in the GET statement.

The first two bytes of *array name* are set to the horizontal (X-axis) number of pixels in the pixel area; the second two bytes are set to the vertical (Y-axis) number of pixels in the pixel area. The remainder of *array name* represents the status of each pixel, either ON or OFF, in the pixel area. The data is stored in a row-by-row format. The data is stored 8 pixels per byte and each row starts on a byte boundary.

Model 4 Computer Graphics

Array Limits

When the array is created, BASICG reserves space in memory for each element of the array. The size of the array is limited by the amount of memory available for use by your program — each real number in your storage array uses four memory locations (bytes).

The array must be large enough to hold your graphic display and the rectangular area must include all the points you want to store.

Your GET rectangular pixel area can include the entire screen (i.e., GET(0,0) – (639,239),array name), if the array is dimensioned large enough.

To determine the minimum array size:

1. Divide the number of X-axis pixels by 8 and round up to the next higher integer.
2. Multiply the result by the number of Y-axis pixels. When counting the X-Y axis pixels, be sure to include the first and last pixel.
3. Add four to the total.
4. Divide by four (for real numbers) or two (for integers) rounding up to the next higher integer.

The size of the rectangular pixel area is determined by the (x,y) coordinates used in GET:

Position: upper-left corner = startpoint = (x1,y1)
 lower-left corner = endpoint = (x2,y2)

Size (in pixels): width = x2 – x1 + 1
 length = y2 – y1 + 1

Example

GET(10,10) – (80,50),V

This block is 71 pixels wide on the X-axis (10 through 80) and 41 long on the Y-axis (10 through 50).

- For real: $71/8 = 9 * 41 = 369 + 4 = 373/4 = 94$
- For integer: $71/8 = 9 * 41 = 369 + 4 = 373/2 = 187$

Depending on the type of array you use, you could set up your minimum-size dimension statement this way:

- Real DIM V(93)

or

- Integer DIM V%(186)

Examples

```
10 DIM V(249)
20 CIRCLE (65,45),20,1
30 GET (10,10) – (120,80),V
```

An array is created, a circle is drawn and stored in the array via the GET statement's rectangular pixel area's parameters (i.e., (10,10) – (120,80)).

Graphics BASIC (BASICG)

Calculate the dimensions of the array this way:

Rectangular pixel area is 111×71 . That equals:

$$111/8 = 14 * 71 = 994 + 4 = 998/4 = 250$$




Figure 11

```
10 DIM V(30,30)
20 CIRCLE (50,50),10
30 GET (10,10)-(80,80),V
```

A two-dimensional array is created, a circle is drawn and stored in the array via the GET statement's rectangular pixel area's parameters (i.e., (10,10)-(80,80)).




Figure 12

```
10 DIM V%(564)
20 CIRCLE (65,45),50,1,1,3
30 GET (10,10)-(120,80),V%
```

A one-dimensional integer array is created, an arc is drawn and stored in the array via the GET statement's rectangular area's parameters.

GLOCATE

Sets the Graphics Cursor

GLOCATE (*x,y*, *direction*)

(*x,y*) specifies the location of the Graphics Cursor and is a pair of integer expressions.

direction specifies the direction that the characters will be written to the Graphics Screen and has an integer value of 0, 1, 2, or 3. *direction* is optional; if omitted, 0 is used.

Since the Text Screen and the Graphics Screen cannot be displayed at the same time, you need an easy way to display textual data on the Graphics Screen. GLOCATE provides part of this function by allowing you to specify where on the Graphics Screen to start displaying the data, (*x,y*), and which direction to display it — *direction*.

The allowable values for *direction* are:

- 0 — zero degree angle
- 1 — 90 degree angle
- 2 — 180 degree angle
- 3 — 270 degree angle

Examples

```
10 GLOCATE (320,120),0
```

This program line will cause characters to be displayed starting in the center of the screen in normal left-to-right orientation.

```
100 GLOCATE (320,10),1
```

This program line will cause characters to be displayed starting in the center of the top portion of the screen in a vertical orientation, going from the top of the screen to the bottom of the screen.

```
200 GLOCATE (630,120),2
```

This program line will cause characters to be displayed upside down starting at the right of the screen and going towards the left.

```
300 GLOCATE (320,230),3
```

This program line will cause the characters to be displayed vertically, starting at the center of the lower portion of the screen towards the top of the screen.

LINE

Draws a Line or Box

LINE (x1,y1)-(x2,y2), c, B or BF, style

(x1,y1) specifies the starting coordinates of a line and is a pair of integer expressions. **(x1,y1)** is optional; if omitted, the last ending coordinates of any previous command are used as the startpoint. If a command has not been previously specified, (0,0) is used.

(x2,y2) specifies the ending coordinates of a line. **(x2,y2)** is a pair of integer expressions.

c specifies the color and is a numeric expression of either 0 or 1. **c** is optional; if omitted, 1 is used.

B or **BF** specifies drawing and/or shading (solid white or solid black) a box. **B** draws a box and **BF** fills a box with shading. **B/BF** is optional; if omitted, only a line is drawn.

style is the setting for the pattern of a line and is a numeric value in the integer range. **style** is optional; if omitted, -1 (solid line) is used. **style** must be omitted if **BF** is used.

LINE draws a line from the starting point $(x1,y1)$ to the ending point $(x2,y2)$.

If the starting point is omitted, either (0,0) is used if a previous end coordinate has not been specified or the last ending point of the previous command is used. If one or both parameters are off the screen, only the part of the line which is visible is displayed.

With over 65,500 line styles possible, each style is slightly different. You'll find it's almost impossible to detect some of the differences since they are so minute.

LINE with Box Option

The *start* and *end* coordinates are the diagonal coordinates of the box (either a square or rectangle). When you don't specify the **B** or **BF** options, the "diagonal" line is drawn. When you specify the **B** option, the perimeter is drawn but not the diagonal line. When you specify the **BF** option, the perimeter is drawn, and the area bounded by the perimeter is shaded in the specified color (*c*).

```
LINE (140,80)-(500,200),1,B
```




Figure 13

Model 4 Computer Graphics

style

style sets the pixel arrangement in 16-bit groups.

For example, 0000 1111 0000 1111 (binary), 0F0F (hex), or 3855 (decimal).

style can be any number in the integer range (negative or positive). Using hexadecimal numbers, you can figure the exact line style you want. There will always be four numbers in the hexadecimal constant.

To use hexadecimal numbers for *style*:

1. Decide what pixels you want OFF (bit=0) and ON (bit=1).
2. Choose the respective hexadecimal numbers (from the Base Conversion Chart, Appendix D).

Example

0000 1111 0000 1111 = &H0F0F

Creates a dashed line.

Type	Binary Numbers	Hex Numbers
Long dash	0000 0000 1111 1111	&H00FF
Short dash	0000 1111 0000 1111	&H0F0F
"Short-short" dash	1100 1100 1100 1100	&HCCCC
Solid line	1111 1111 1111 1111	&HFFFF
OFF/ON	0101 0101 0101 0101	&H5555
"Wide" dots	0000 1000 0000 1000	&H0808
Medium dots	1000 1000 1000 1000	&H8888
Dot-dash	1000 1111 1111 1000	&H8FF8

Table 5. Sample Line Styles

Examples

LINE - (100,40)

This example draws a line in white (ON) starting at the last endpoint used and ending at (100,40).

LINE (0,0) - (319,199)

This statement draws a white line starting at (0,0) and ending at (319,199).

LINE (100,100) - (200,200), 1, ,45

This example draws a line from (100,100) to (200,200) using line style 45 (&H002D).

Graphics BASIC (BASICG)

```
LINE (100,100)-(300,200),1,,&H00FF
```

This LINE statement draws a line with "long dashes." Each dash is eight pixels long and there are eight blank pixels between each dash.

```
LINE (100,100)-(300,200),1,-1000
```

This statement draws a line from (100,100) to (300,200) using line style -1000.

```
LINE (200,200)-(-100,100)
```

A line is drawn from the startpoint of (200,200) to (-100,100).

```
10 LINE (30,30)-(180,120)
```

```
20 LINE -(120,180)
```

```
30 LINE -(30,30)
```

This program draws a triangle.

```
10 LINE -(50,50)
```

```
20 LINE -(120,80)
```

```
30 LINE -(-100,-100)
```

```
40 LINE -(3000,1000)
```

This program draws four line segments using each endpoint as the startpoint for the next segment.

PAINT Paints Screen

PAINT (x,y), *tiling*, *border*, *background*

(x,y) specifies the X-Y coordinates where painting is to begin. *x* is a numeric expression from 0 to 639 and *y* is a numeric expression from 0 to 239.

tiling specifies the paint style and can be a string or a numeric expression. *tiling* is optional; if omitted, 1 is used. *tiling* cannot be a null string (" ") and no more than 64 bytes may be contained in the *tiling* string.

border specifies the OFF/ON color of the border where painting is to stop and is a numeric expression of either 0 (OFF) or 1 (ON). *border* is optional; if omitted, 1 is used.

background specifies the color of the background that is being painted and is a 1-byte string of either 0 (CHR\$(&H00)) or 1 (CHR\$(&HFF)). *background* is optional; if omitted, CHR\$(&H00) is used.

PAINT shades the Graphics Screen with *tiling* starting at the specified X-Y coordinates, proceeding upward and downward.

x,y

Paint Startpoint

x,y is the coordinate where painting is to begin and must:

- Be inside the area to be painted.
- Be on the working area of the screen.

For example:

```
10 CIRCLE(320,120),80
20 PAINT(320,120),1,1
```

A circle with a centerpoint of (320,120) is drawn and painted in white.

tiling

Paint Style

tiling is the pattern in a graphics display. By specifying each pixel, you can produce a multitude of tiling styles thereby simulating different shades of paint on the screen.

tiling is convenient to use in bar graphs, pie charts, etc., or whenever you want to shade with a defined pattern.

There are two types of *tiling*:

- Numeric expressions
- Strings

Numeric Expressions. There are only two numeric expressions that can be used for the paint style — 0 and 1. 1 paints all pixels ON (solid white) and 0 paints all pixels OFF (solid black).

To use numeric expressions, enter either a 0 or 1. For example:

```
PAINT (320,120),1,1
```

Strings (Point-by-Point Painting). You can paint precise patterns using strings by defining a multi-pixel grid, pixel-by-pixel, on your screen as one contiguous pattern.

String painting is called “pixel” painting because you are literally painting the screen “pixel-by-pixel” in a predetermined order.

You can define the tile length as being one to 64 vertical tiles, depending on how long you want your pattern. Tile width, however, is always eight horizontal pixels (8 pixels representing one 8-bit byte). The dimensions of a tile pattern are length by width. Tile patterns are repeated as necessary to paint to the specified borders. Because of its symmetry, you'll probably find equilateral pixel grids most convenient.




Figure 14. Example of an 8-by-8 Pixel Grid

Strings allow numerous graphic variations because of the many pixel combinations you can define.

Important Note: You cannot use more than two consecutive rows of tiles which match the background or an Illegal Function Call error will occur. For example:

```
PAINT (1,1),CHR$(&HFF)+CHR$(&HFF)+CHR$(&H00)+CHR$(&H00)  
+CHR$(&H00)+CHR$(&H00),1,CHR$(&H00)
```

returns an Illegal Function Call error.

Using Tiling

You may want to use a sheet of graph paper to draw a style pattern. This way, you'll be able to visualize the pattern and calculate the binary and hexadecimal numbers needed.

Note: Tiling should only be done on either a totally black or white background; otherwise, results are unpredictable.

To draw an example of a tile on paper:

1. Take a sheet of paper and draw a grid according to the size you want (8×8 , 24×8 , etc.). Each boxed area on this grid, hypothetically, represents one pixel on your screen.
2. Decide what type of pattern you want (zigzag, diagonal lines, perpendicular lines, etc.).
3. Fill in each grid in each 8-pixel-wide row of the tile if you want that pixel to be ON, according to your pattern. If you want the pixel to be OFF, leave the grid representing the pixel blank.
4. On your paper grid, count each ON pixel as 1 and each OFF pixel as 0. List the binary numbers for each row to the side of the grid. For example, you might have 0001 1000 on the first row, 0111 0011 on the second row, etc.
5. Using a hexadecimal conversion chart, convert the binary numbers to hexadecimal numbers. (Each row equates to a two-digit hexadecimal number.)
6. Insert the hexadecimal numbers in a tile string and enter the string in your program.

Note: For a listing of commonly used tiling styles, see Appendix E.

Example

For example, if you're working on an 8×8 grid and want to draw a plus ('+' sign):

								Binary	Hex
0	0	0	1	1	0	0	0	0001 1000	18
0	0	0	1	1	0	0	0	0001 1000	18
0	0	0	1	1	0	0	0	0001 1000	18
1	1	1	1	1	1	1	1	1111 1111	FF
1	1	1	1	1	1	1	1	1111 1111	FF
0	0	0	1	1	0	0	0	0001 1000	18
0	0	0	1	1	0	0	0	0001 1000	18
0	0	0	1	1	0	0	0	0001 1000	18

Figure 15. 8×8 Grid

Tile string:

```
A$=CHR$(&H1B)+CHR$(&H1B)+CHR$(&H1B)+CHR$(&HFF)+CHR$(&HFF)
    +CHR$(&H1B)+CHR$(&H1B)+CHR$(&H1B)
```

b Border

Border is the OFF/ON color of the border of a graphics design where painting is to stop and is a numeric expression of either 0 or 1. If omitted, 1 (ON) is used and all the pixels on the border are set (solid white).

background Background Area

Background is a 1-byte character which describes the background of the area you are painting. CHR\$(&H00) specifies a black background and CHR\$(&HFF) is a totally white background. If background is not specified, BASICG uses CHR\$(&H00).

Painting continues until a border is reached or until PAINT does not alter the state of any pixels in a row. However, if pixels in a given row are not altered and the tile that was to be painted in that row matches the background tile, painting will continue on to the next row.

Note: BASICG uses Free Memory for tiling.

Examples

```
10 CIRCLE (300,100),100
20 PAINT (300,100),1,1
```

Paints the circle in solid white.

```
10 CIRCLE (100,100),300
20 PAINT (100,100),1,1
```

Paints the circle. Only the visible portion of the circle is painted on the screen.

```
4 CLR
5 A=1
6 SCREEN 0
10 CIRCLE (320,120),100
20 CIRCLE (100,100),50
30 CIRCLE (400,200),60
40 CIRCLE (500,70),50
50 PAINT (320,120),A,1
60 PAINT (100,100),A,1
70 PAINT (400,200),A,1
80 PAINT (500,70),A,1
```

The tiling style is assigned the value 1 in line 5 (A=1) for all PAINT statements. Four circles are drawn and painted in solid white.

```
10 LINE (140,80)-(500,200),1,B
20 PAINT (260,120),CHR$(&HEE)+CHR$(&H77)+CHR$(&00),1
```

Paints box in specified tiling style using strings.

```
10 CIRCLE (300,100),100
20 PAINT (300,100),"D",1
```

This example uses a character constant to paint the circle in vertical blank and white stripes. The character "D" (0100 0100) sets this vertical pattern: one vertical row of pixels ON, three rows OFF.

```
10 CIRCLE (320,120),200
20 PAINT (320,120),"332211",1
30 PAINT (100,70),"EFEF",1
```

This example draws and paints a circle, then paints the area surrounding the circle with a different paint style (line 30). This PAINT statement's (line 30) startpoint must be outside the border of the circle.

```
10 PAINT (320,120),CHR$(&HFF),1
20 CIRCLE (320,120),100,0
30 PAINT (320,120),CHR$(&0)+CHR$(&HFF),0,CHR$(&HFF)
```

Paints the screen white, draws a circle and paints the circle with a pattern.

```
10 PAINT (320,120),CHR$(&HFF),1
20 CIRCLE (320,120),100,0
30 PAINT (320,120),CHR$(&0)+CHR$(&HAA),0,CHR$(&HFF)
```

Paints the screen white, draws a circle and paints the circle with a pattern.

Model 4 Computer Graphics

```
10 CIRCLE(300,100),100
20 A$=CHR$(&H00)+CHR$(&H7E)+CHR$(&H18)+CHR$(&H18)+CHR$(&H18)
   +CHR$(&H18)+CHR$(&H18)+CHR$(&H00)
30 PAINT(300,100),A$,1
```

This draws the circle and paints with the letter T within the parameters of the circle.

```
10 A$=CHR$(&H41)+CHR$(&H22)+CHR$(&H14)+CHR$(&H08)+CHR$(&H14)
   +CHR$(&H22)+CHR$(&H41)+CHR$(&H00)
20 PAINT (300,100),A$, 1
```

This paints Xs over the entire screen.

```
1 CLEAR 100
3 CLR
5 SCREEN 0
10 TILE$(0)=CHR$(&H22)+CHR$(&H00)
20 TILE$(1)=CHR$(&HFF)+CHR$(&H00)
30 TILE$(2)=CHR$(&H99)+CHR$(&H66)
40 TILE$(3)=CHR$(&H99)
50 TILE$(4)=CHR$(&HFF)
60 TILE$(5)=CHR$(&HF0)+CHR$(&HF0)+CHR$(&H0F)+CHR$(&H0F)
70 TILE$(6)=CHR$(&H3C)+CHR$(&H3C)+CHR$(&HFF)
80 TILE$(7)=CHR$(&H03)+CHR$(&H0C)+CHR$(&H30)+CHR$(&HC0)
90 A$=TILE$(0)+TILE$(1)+TILE$(2)+TILE$(3)+TILE$(4)
   +TILE$(5)+TILE$(6)+TILE$(7)
100 PAINT(300,100),A$1
```

This example paints the screen with a tiling pattern made up of eight individually defined tile strings (0-7).

&POINT (function) Returns Pixel Value

&POINT(x,y)

x specifies an X-coordinate and is an integer expression.

y specifies a Y-coordinate and is an integer expression.

values returned by &POINT are:

0 (pixel OFF)

1 (pixel ON)

-1 (pixel is off the screen)

The &POINT command lets you read the OFF/ON value of a pixel from the screen.

Values for &POINT that are off the screen (i.e., PRINT &POINT (800,500)) return a -1, signifying the pixel is off the screen.

Graphics BASIC (BASICG)

Example

```
10 PSET(300,100),1
20 PRINT &POINT(300,100)
```

Reads and prints the value of the pixel at the point's coordinates (300,100) and displays its value: 1.

```
PRINT &POINT(3000,1000)
```

Since the pixel is off the screen, a -1 is returned.

```
PRINT &POINT(-3000,1000)
```

Since the pixel is off the screen, a -1 is returned.

```
PSET(200,100),0
PRINT &POINT(200,100)
```

Reads and prints the value of the pixel at the point's coordinates (200,100) and displays its value: 0.

```
10 PSET(300,100),1
20 IF &POINT(300,100)=1 THEN PRINT "GRAPHICS BASIC!"
```

Sets the point ON. Since the point's value is 1, line 20 is executed and Graphics BASIC is displayed:

```
GRAPHICS BASIC!
```

```
5 SCREEN 0
10 PSET(RND(640),RND(240)),1
20 IF &POINT(320,120)=1 THEN STOP
30 GOTO 10
```

Sets points randomly until (320,120) is set.

```
5 CLR
10 LINE(50,80)-(120,100),1,BF
20 PRINT &POINT(100,80)
30 PRINT &POINT(110,80)
40 PRINT &POINT(115,90)
50 PRINT &POINT(50,40)
60 PRINT &POINT(130,120)
```

The first three pixels are in the filled box, so the value 1 (one) is displayed for each of the statements in lines 20, 30, and 40. The pixels specified in lines 50 and 60 are not in the shaded box and 0s are returned.

PRESET

Sets Pixel OFF (or ON)

PRESET(x,y),switch

x specifies an X-coordinate and is an integer expression.

y specifies a Y-coordinate and is an integer expression.

switch specifies a pixel's OFF/ON code and is an integer of either 0 (OFF) or 1 (ON).

switch is optional; if omitted, 0 (OFF) is used.

PRESET sets a pixel either OFF (0) or ON (1), depending on *switch*. If *switch* is not specified, 0 (OFF) is used.

Values for (x,y) that are larger than the parameters of the screen (i.e., greater than 639 for x and 239 for y) are accepted, but these points are off the screen and therefore are not PRESET.

Note: The only choice for *switch* is 0 or 1. If you enter any other number, an Illegal Function Call error will result.

Examples

```
10 PRESET (50,50),1
20 PRESET (50,50),0
```

Turns ON the pixel located at the specified coordinates (in line 10) and turns the pixel OFF (in line 20).

```
5 SCREEN 0
10 PRESET (320,120),1
20 PRESET (300,100),1
30 PRESET (340,140),1
40 FOR I=1 TO 1000: NEXT I
50 PRESET (320,120)
60 PRESET (300,100)
70 PRESET (340,140)
80 FOR I=1 TO 1000: NEXT I
```

Sets the three specified pixels ON (through the three PRESET statements), pauses, and then turns the three pixels OFF.

```
PRESET(3000,1000),1
```

The values for (x,y) are accepted, but since the coordinates are beyond the parameters of the screen, the point is not PRESET.

PRINT #-3, Write Text Characters to the Graphics Screen

PRINT #-3, item list

item list may be either string constants (messages enclosed in quotes), string variables, numeric constants (numbers), variables, or expressions involving all of the preceding items. The items to be printed may be separated by commas or semicolons. If commas are used, the Cursor automatically advances to the next print zone before printing the next item. If semicolons are used, a space is not inserted between the items printed on the screen. In cases where no ambiguity would result, all punctuation can be omitted.

PRINT #-3, is used to write text characters to the Graphics Screen. This is the easiest way to display textual data on the Graphics Screen. Characters are displayed starting at the current Graphics Cursor and going in the direction specified by the most recently executed GLOCATE command. If a GLOCATE command was not executed prior to the PRINT #-3, command, a direction of 0 is assumed.

PRINT#-3, will only print text characters (see Appendixes of the *Model 4 Disk System Owner's Manual*). Each character displayed in the 0 or 2 direction uses an 8 × 8 pixel grid; each character displayed in the 1 or 3 direction uses a 16 × 8 grid. Executing this command will position the Graphics Cursor to the end of the last character that was displayed.

Displaying text in direction 0 engages a wraparound feature. If the end of a line is reached, BASICG will continue the display on the next line. If the end of the screen is reached, BASICG will continue the display at the beginning of the screen without scrolling. If there is not enough room to display at least one character at the current Graphics Cursor, an Illegal Function Call error will result. When displaying text in other directions, an attempt to display text outside of the currently defined screen will cause an Illegal Function Call error to be given.

PSET Sets Pixel ON (or OFF)

PSET(x,y),switch

x specifies an X-coordinate and is an integer expression.

y specifies a Y-coordinate and is an integer expression.

switch specifies a pixel's OFF/ON color code and is a numeric expression of 0 (OFF) or 1 (ON).

switch is optional; if omitted, 1 (ON) is used.

PSET sets a pixel either OFF (0) or ON (1), depending on *switch*. If *switch* is not specified, 1 (ON) is used.

The only choice for *switch* with PSET is 0 and 1. If you enter any other number, an Illegal Function Call will occur.

Values for (x,y) that are larger than the parameters of the screen (i.e., greater than 639 for x and 239 for y) are accepted, but these points are off the screen and therefore are not PSET.

Note: The only distinction between PRESET and PSET in BASICG is the default value for *switch*. The default value for PRESET is 0, while the value for PSET is 1.

Model 4 Computer Graphics

Examples

```
10 A=1
20 PSET (50,50),A
```

Turns the pixel located at the specified coordinates ON.

```
10 PSET (RND(640),RND(240)),1
20 GOTO 10
```

Pixels are randomly set to 1 (ON) over the defined area (the entire screen).

```
PSET (-300,-200),1
```

The values for (x,y) are accepted, but since it is beyond the parameters of the screen, the pixel is not set.

```
10 PSET (320,120),1
20 A$=INKEY$: IF A$= " " THEN 20
30 PSET(320,120),0
```

Line 10 sets ("turns ON") a pixel; line 30 resets ("turns OFF") the same dot.

PUT

Puts Rectangular Pixel Area from Array onto Screen

PUT (x1,y1), array name, action

(x1,y1) are coordinates of the upper-left corner of the rectangular pixel area which is to contain a graphic display. *x1* is a numeric expression from 0 to 639 and *y1* is a numeric expression from 0 to 239.

array name is the name of an array (previously specified by GET) that contains the data to be written into the rectangular pixel area.

action determines how the data is written into the rectangular pixel area and is one of the following:

PSET	Sets or resets each point in the specified pixel area to the value in the specified array.
PRESET	Sets or resets each point in the specified pixel area to the inverse of the value in the specified array.
XOR	Performs a logical exclusive-OR between the bits in the specified array and the pixels in the destination area and displays the result.
OR	Performs a logical OR between the bits in the specified array and the pixels in the destination area and displays the result.
AND	Performs a logical AND between the bits in the specified array and the pixels in the destination area and displays the result.

action is optional; if omitted, XOR is used.

Important Note: BASICG recognizes two syntaxes of the command PUT — the syntax described in this manual and the syntax described in the *Model 4 Disk System Owner's Manual*. BASIC recognizes only the PUT syntax described in the *Model 4 Disk System Owner's Manual*.

Graphics BASIC (BASICG)

The PUT function puts a rectangular pixel area stored in an array, and defined by GET, onto the screen. GET and PUT work jointly. Together, they allow you to "get" a rectangular pixel area which contains a graphic display, store it in an array, then "put" the array back on the screen later.

Remember that before you GET or PUT, you have to create an array to store the bit contents of the display rectangular pixel area. The size of the array must match that of the display rectangular pixel area.

PUT moves your GET rectangular pixel area to the startpoint in your PUT statement and the startpoint is the new upper-left corner of the rectangular pixel area.

To illustrate:

```
5 DIM V(3)
10 GET (2,3)-(7,7),V
100 PUT 50,50),V,PSET
```

After GETting, PUT this rectangular pixel area to (50,50). The new coordinates are:

```
(50,50) (51,50) (52,50) (53,50) (54,50) (55,50)
(50,51) (51,51) (52,51) (53,51) (54,51) (55,51)
(50,52) (51,52) (52,52) (53,52) (54,52) (55,52)
(50,53) (51,53) (52,53) (53,53) (54,53) (55,53)
(50,54) (51,54) (52,54) (53,54) (54,54) (55,54)
```

The rectangular pixel area ((50,50) – (55,54)) is exactly the same pixel size as (2,3) – (7,7); only the location is different.




Figure 16

With PUT, action can be PSET, PRESET, OR, AND, or XOR.

These operators are used in BASICG to test the OFF/ON (or 0/1) conditions of a pixel in the original pixel area and the destination pixel area.

Model 4 Computer Graphics

For example (using PSET), the pixel is set ON only if the bit in the PUT array is set ON. If the bit is OFF, the pixel is turned OFF (reset).

With PRESET, the pixel is set ON only if the bit in the PUT array is set OFF. If the bit is ON, the pixel is turned OFF (reset).

Using OR, the pixel is set ON if the bit in the PUT array is ON or the corresponding pixel in the destination area is ON. In all other cases, the pixel is turned OFF (reset). In other words:

OR	OFF	ON
OFF	OFF	ON
ON	ON	ON

With AND, the pixel is set ON, if both the bit in the PUT array and the corresponding pixel in the destination area are ON. In all other cases, the pixel is turned OFF (reset). In other words:

AND	OFF	ON
OFF	OFF	OFF
ON	OFF	ON

Using XOR, the pixel is set ON if either the bit in the PUT array or the corresponding pixel in the destination area (but not both) is ON. In all other cases, the pixel is turned OFF (reset). In other words:

XOR	OFF	ON
OFF	OFF	ON
ON	ON	OFF

The following BASICG program will graphically illustrate the differences between the various action options. Since the program will give you a "hard-copy" printout of the action options, you'll need to connect your TRS-80 to a graphic printer. See "Graphics Utilities" later in this manual for more details on using the Computer Graphics package with a printer.

Graphics BASIC (BASICG)

```
10 DATA "OR", "AND", "PRESET", "PSET", "XOR"
20 CLR : SCREEN 0
30 FOR Y= 10 TO 210 STEP 50
40 FOR X= 0 TO 400 STEP 200
50 LINE (X+40,Y-5)-(X+100,Y+25),1,B
60 NEXT X
70 LINE (50,Y)-(90,Y+10),1,BF
80 FOR X= 200 TO 400 STEP 200
90 LINE (X+50,Y)-(X+70,Y+20),1,BF
100 NEXT X
110 NEXT Y
120 DIM V(100)
130 GET (50,10)-(90,30),V
140 FOR N=1 TO 5
150 R= (N-1)*5+1
160 READ A$
165 GLOCATE (136,R*10),0
170 PRINT #3, A$;
175 GLOCATE (360,R*10),0
180 PRINT #3, "=";
190 ON N GOTO 200, 210, 220, 230, 240
200 PUT (450,10), V,OR: GOTO 250
210 PUT (450,60), V,AND: GOTO 250
220 PUT (450,110), V,PRESET: GOTO 250
230 PUT (450,160), V,PSET: GOTO 250
240 PUT (450,210), V,XOR
250 NEXT N
260 SYSTEM "GPRINT"
270 SCREEN 1
```




Figure 17

Hints and Tips about PUT:

- An Illegal Function Call error will result if you attempt to PUT a rectangular pixel area to a section of the screen which is totally or partially beyond the parameters of the screen. For example:

```
GET(50,50)-(150,150),V
PUT(200,200),V,PSET
```

returns an error because the rectangular pixel area cannot be physically moved to the specified rectangular pixel area (i.e., (200,200) – (300,300)).

- If you use PUT with a viewport (see VIEW), all coordinates must be within the parameters of the viewport or you'll get an Illegal Function Call error.

Examples

PUT with PSET

```
10 DIM V%(63)
15 SCREEN 0
17 CLR
20 CIRCLE (30,30),10
30 GET (10,10)-(40,40),V%
40 FOR I=1 TO 500: NEXT I
50 CLR
60 PUT (110,110),V%,PSET
70 FOR I=1 TO 500: NEXT I
```

In this example, the circle is drawn, stored, moved and re-created. First the white-bordered circle appears in the upper left corner of the screen (position (30,30) — program line 20). After a couple of seconds (because of the delay loop), it disappears and then reappears on the screen — (110,110) — program line 60.

What specifically happened is:

1. An array was created (line 10).
2. A circle was drawn (line 20).
3. GET — The circle which was within the source rectangular pixel area, as specified in the GET statement's parameters is stored in the array (line 30).
4. The screen is cleared (line 50).
5. PUT — The circle from the array was PUT into the destination rectangular pixel area as specified in the PUT statement (line 60) with the PSET option.

Graphics BASIC (BASICG)

```
5 SCREEN 0
6 CLR
10 DIM V%(700)
20 LINE (20,20)-(20,80)
30 LINE (80,0)-(80,80)
40 LINE (30,30)-(30,80)
50 LINE (10,5)-(10,80)
60 GET (0,0)-(100,100),V%
70 FOR I=1 TO 1000: NEXT I
80 PUT (180,120),V%,PSET
90 FOR I=1 TO 1000: NEXT I
```

Draws four lines. GET stores the lines in the rectangular pixel area. PUT moves the lines to another rectangular pixel area.

SCREEN Selects Screen

SCREEN type

type specifies which "Screen" to use and is a numeric expression of either 0 or 1.

0 = Graphics Screen

1 = Text Screen

SCREEN lets you set the proper screen. SCREEN 0 selects the Graphics Screen; SCREEN 1 selects the Text Screen. Any value other than 0 or 1 with SCREEN gives an error.

SCREEN is convenient to use when you want to display either a Graphics Screen or a Text Screen. For example, you may have run a program and then added to it. With SCREEN, you can remove the graphics display, add to the program, and then return to the Graphics Screen.

Whenever BASICG tries to display a character on the Text Screen (like in an INPUT or PRINT statement), the screen is automatically set to the Text Screen. If the program is still running after executing the statement, BASICG will revert to the screen that was in effect prior to executing the statement.

Examples

```
10 SCREEN 1
20 LINE (150,150)-(200,200)
```

The computer executes the short program but the Graphics Screen cannot display the graphics because of the SCREEN 1 command. To display the line, type: SCREEN 0 **(ENTER)**

Model 4 Computer Graphics

```
10 CLR
20 SCREEN 1
30 LINE(10,10)-(255,191)
40 LINE(0,191)-(255,0)
50 A$=INKEY$: IF A$="" THEN 50
60 SCREEN 0
70 A$=INKEY$: IF A$="" THEN 70
80 GOTO 10
```

The computer executes the program (draws two intersecting lines) but the screen cannot display the graphics because of SCREEN 1. By pressing any key, the graphics are displayed because of SCREEN 0.

```
5 CLR
10 CIRCLE(200,100),100
20 PAINT (200,100),"44",1
```

Now run the program and type:

SCREEN 0 (ENTER)

This command turns the Graphics Screen ON. By entering the SCREEN 1 and SCREEN 0 commands, you can alternately turn the Graphics Screen OFF and ON without losing the executed program display.

VIEW (Command)

Redefines the Screen (Creates a Viewport)

VIEW (x1,y1)-(x2,y2), c, b

(x1,y1) are coordinates of the upper-left corner of a rectangular viewport area. *x1* is an integer expression between 0 and 639. *y1* is an integer expression between 0 and 239.
(x2,y2) are coordinates of the lower-right corner of a rectangular viewport area. *x2* is an integer expression \geq to *x1* and \leq 639. *y2* is an integer expression \geq *y1* and \leq 239.
c specifies the color of the interior of the viewport and is an integer expression of either 0 or 1. *c* is optional; if omitted, the viewport is not shaded.
b specifies the border color of the viewport and is a numeric expression of either 0 or 1. *b* is optional; if omitted, a border is not drawn.

VIEW creates a "viewport" which redefines the screen parameters (0-639 for X and 0-239 for Y). This defined area then becomes the only place you can draw graphics displays.

If you enter more than one viewport, you can only draw displays in the last defined viewport.

Since VIEW redefines the SCREEN:

- CLR clears the interior of the viewport only.
- If you PSET or PRESET points, draw circles, etc., beyond the parameters of the currently defined viewport, only the portions that are in the viewport will be displayed.
- If you try to read a point beyond the viewport (with POINT), it will return a -1.
- You can only GET and PUT arrays within the viewport.
- You can't PAINT outside the viewport.

Graphics BASIC (BASICG)

The upper-left corner of the viewport is read as (0,0) (the "relative origin") when creating items inside the viewport. All the other coordinates are read relative to this origin. However, the "absolute coordinates" of the viewport, as they are actually defined on the Graphics Cartesian system, are retained in memory and can be read using VIEW as a function.

Every viewport has absolute and relative coordinates and graphic displays are drawn inside using the relative coordinates. For example:

```
10 VIEW (100,100)-(200,200),0,1
20 LINE (30,15)-(80,60),1
```




Figure 18

Note: After each of the following examples, you'll have to redefine the entire screen to VIEW (0,0)-(639,239) before performing any other Graphics functions.

Examples

```
VIEW (100,100)-(200,200),0,1
```

Draws a black viewport (pixels OFF) that is outlined in white (border pixels ON).

```
VIEW (100,100)-(200,200),1,1
```

Draws a white viewport (pixels ON) that is outlined in white (border pixels ON).

```
VIEW (50,50)-(100,100),1,0
```

Draws a white viewport (pixels ON) that is outlined in black (border pixels OFF).

```
10 VIEW (10,10)-(600,200),0,1
20 VIEW (50,50)-(100,100),0,1
30 LINE(RND(500),RND(190))-(RND(500),RND(190))
40 GOTO 30
```

First you defined a large viewport that almost covered the entire screen. Next you defined a smaller viewport. The Random command draws lines within the specified parameters but only the segments of the lines that are within the parameters of the smaller viewport are visible since it was specified last.

```
10 VIEW(80,80)-(400,200),0,1
20 VIEW(100,90)-(300,170),0,1
30 VIEW(120,100)-(200,200),0,1
40 VIEW(50,50)-(100,100),0,1
```

Draws four viewports. All further drawing takes place in the last viewport specified.

Model 4 Computer Graphics

```
10 VIEW(210,80)-(420,160),0,1
20 CIRCLE(300,120),180,1
30 LINE(15,15)-(60,60),1
40 CIRCLE(90,40),50,1
50 LINE(40,30)-(500,30),1
```

Draws a viewport. Draws a circle but only a portion is within the parameters of the viewport. This circle's centerpoint is relative to the upper left corner of the viewport and not to the absolute coordinates of the graphics Cartesian system. A line is drawn which is totally within the parameters of the viewport. Another circle is drawn which is totally within the parameters of the viewport. Another line is drawn which is only partially within the parameters of the viewport.

```
10 VIEW (190,70)-(440,180),0,1
20 CIRCLE (300,140),170,1
30 CIRCLE (100,230),400,1
40 LINE (10,10)-(500,230),1
```

Draws a viewport. A circle is drawn but only a portion is within the parameters of the viewport. Another circle is drawn and a larger portion is within the parameters of the viewport. A line is drawn but only a segment is within the parameters of the viewport.

&VIEW (function) Returns Viewport Coordinates

&VIEW (p)

(p) specifies a coordinate on the X- or Y-axis and is an integer expression between 0–3. 0 returns the left X-coordinate of your viewport. 1 returns the upper Y-coordinate. 2 returns the right X-coordinate. 3 returns the lower Y-coordinate.

&VIEW returns a corner coordinate of a viewport. It is important to note the parentheses are not optional. If you enter the &VIEW function without the parentheses, a Syntax Error will result.

To display one of the four viewport coordinates, you must enter one of the following values for *p*:

- 0 returns the upper left X-coordinate
- 1 returns the upper left Y-coordinate
- 2 returns the lower right X-coordinate
- 3 returns the lower right Y-coordinate

Important Note: When you have defined several viewports, &VIEW only returns the coordinates of the last-defined viewport.

Examples

Set up the following viewport:

```
VIEW(100,80)-(220,150),0,1
```

Now type: PRINT &VIEW(0) (ENTER)

Displays: 100

Type: PRINT &VIEW(1) (ENTER)

Displays: 80

Enter: PRINT &VIEW(2) (ENTER)

Displays: 220

Type: PRINT &VIEW(3) (ENTER)

Displays: 150

Set up the following viewports:

```
VIEW(100,80)-(220,150),0,1 (ENTER)
```

```
VIEW(250,170)-(350,220),0,1 (ENTER)
```

Now enter: PRINT &VIEW(0) (ENTER)

Displays: 250

Type: PRINT &VIEW(1) (ENTER)

Displays: 170

Now type: PRINT &VIEW(2) (ENTER)

Displays: 350

Type: PRINT &VIEW(3) (ENTER)

Displays: 220

3/ Graphics Utilities

There are eight utilities included with the TRS-80 Computer Graphics package which are intended to be used as stand-alone programs. However, if you are an experienced programmer, you can use these with BASICG and FORTRAN. The source-code for each utility, that illustrates Graphics programming techniques, is listed later in this section.

The Graphics Utilities let you:

- Save graphic displays to diskette.
- Load graphic displays from diskette.
- Print graphic displays on a graphics printer.
- Turn graphics display OFF or ON.
- Clear graphics memory.

To use these utilities from BASICG, use the SYSTEM command followed by the name of the utility in quotation marks (e.g., SYSTEM"GCLS" **(ENTER)**) and control returns to BASIC Ready. From TRSDOS, enter the utility directly, without quotation marks (e.g., GCLS **(ENTER)**).

To call these routines from FORTRAN, see the Subprogram Linkage section of your *TRS-80 Model 4 FORTRAN Manual* (26-2219).

Utilities	
Command	Action
GCLS	Clears graphics screen.
GLOAD	Loads graphics memory from diskette.
GPRINT	Lists graphics on the printer.
GPRT2	Prints graphic display on the printer without 90 degree rotation.
GPRT3	Prints graphic display on the printer without 90 degree rotation.
GROFF	Turns Graphic Screen OFF.
GRON	Turns Graphic Screen ON.
GSAVE	Saves graphics memory to diskette.

Table 6

GCLS Clears Graphics Screen

GCLS

GCLS clears the Graphics Screen by erasing the contents of graphics memory corresponding to the visible Graphics Screen. GCLS erases graphics memory by writing zeroes (OFF) to every bit in memory. GCLS does not clear the Text Screen (video memory).

Examples

When TRSDOS Ready is displayed, type:

```
GCLS (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GCLS" (ENTER)
```

or

```
100 SYSTEM"GCLS"
```

GLOAD

Loads Graphics Memory from Diskette

GLOAD filename /ext .password :d

filename consists of a name of up to eight characters; the first character must be a letter.

/ext is an optional name-extension; *ext* is a sequence of up to three numbers or letters.

.password is an optional password; *password* is a name of up to eight characters; the first character must be a letter.

:d is an optional drive specification; *d* is one of the digits 0 through 3.

Note: There cannot be spaces within a file specification. TRSDOS terminates the file specification at the first space.

With GLOAD, you can load TRSDOS files that have graphic contents into graphics memory. These files must have been previously saved to diskette using GSAVE.

Examples

When TRSDOS Ready is displayed, type:

```
GLOAD PROGRAM/DAT.PASSWORD:0 (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GLOAD PROGRAM" (ENTER)
```

or

```
100 SYSTEM "GLOAD PROGRAM"
```

GPRINT

Lists Graphic Display to Printer

GPRINT

GPRINT lets you print graphics memory on a graphics (dot-addressable) printer, such as Radio Shack's DMP-100 (26-1253) or DMP-200 (26-1254). Both of these printers have a 9½" carriage. However, distortion will occur when

Graphic routines are printed with GPRINT. This is because GPRINT is not a true pixel-by-pixel "Screen Dump" since the pixel size and spacing on the screen is different from the pixel size and spacing on the Printer. GPRINT is a point of departure for you to obtain hard-copy representations of graphics.

To print graphic displays, GPRINT turns the contents of the Graphic Screen clockwise 90 degrees and then prints.

However, FORMS must be used to set printing parameters.

See your *Model 4 Disk System Owner's Manual* and printer owner's manual for details on setting printing parameters.

Important Note! Do not press **(BREAK)** while GPRINT is executing.

Examples

When TRSDOS Ready is displayed, type:

```
GPRINT (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GPRINT" (ENTER)
```

or

```
100 SYSTEM"GPRINT"
```

For a complete GPRINT sample session, see **Appendix D**.

GPRT2 Print Graphics

GPRT2

GPRT2 is similar to GPRINT but is designed for use with wide-carriage (15") printers such as the DMP-400 and DMP-500.

GPRT2 is different from GPRINT in that the image is not rotated 90 degrees and a different aspect ratio is used.

If GPRT2 does not produce the quality of printout you desire, try GPRT3 or GPRINT.

Important Note! Do not press **(BREAK)** while GPRT2 is executing.

Examples

When TRSDOS Ready is displayed, type:

```
GPRT2 (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GPRT2" (ENTER)
```

or

```
100 SYSTEM"GPRT2"
```

GPRT3

Print Graphics (Double on the Y-Axis)

GPRT3

GPRT3 is similar to GPRINT but is designed for use with wide-carriage (15") printers such as the DMP-400 and DMP-500.

GPRT3 is different from GPRINT in that the image is not rotated 90 degrees and a different aspect ratio is used.

If GPRT3 does not produce the quality of print-out you desire, try GPRT2 or GPRINT.

Important Note! Do not press **(BREAK)** while GPRT3 is executing.

Examples

When TRSDOS Ready is displayed, type:

```
GPRT3 (ENTER)
```

or when the BAISCG READY prompt is displayed, type:

```
SYSTEM"GPRT3" (ENTER)
```

or

```
100 SYSTEM"GPRT3"
```

GROFF

Turns Graphics Display OFF

GROFF

GROFF turns the Graphics Screen OFF. GROFF is different from GCLS since GROFF simply removes the Graphics display without erasing the contents of graphic memory. GCLS completely clears graphics memory by writing zeroes (OFF) to every bit in memory.

Examples

When TRSDOS Ready is displayed, type:

```
GROFF (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GROFF" (ENTER)
```

or

```
100 SYSTEM"GROFF"
```

GRON

Turns Graphics Display ON

GRON

GRON turns the Graphics Screen ON.

Examples

When TRSDOS Ready is displayed, type:

```
GRON (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GRON" (ENTER)
```

or

```
100 SYSTEM"GRON"
```

GSAVE

Saves Graphics Memory to Diskette

GSAVE *filename* /*ext* .*password* :*d*

filename consists of a name of up to eight characters; the first character must be a letter.

/ext is an optional name-extension; *ext* is a sequence of up to three numbers or letters.

.password is an optional password; *password* is a name of up to eight characters; the first character must be a letter.

:d is an optional drive specification; *d* is one of the digits 0 through 3.

Note: There cannot be spaces within a file specification. TRSDOS terminates the file specification at the first space.

With GSAVE, the contents in graphics memory is saved under a specified *filename* which follows the standard TRSDOS format. To load the file back into memory, use GLOAD.

Examples

When TRSDOS Ready is displayed, type:

```
GSAVE PROGRAM/DAT.PASSWORD:0 (ENTER)
```

or when the BASICG READY prompt is displayed, type:

```
SYSTEM"GSAVE PROGRAM" (ENTER)
```

or

```
100 SYSTEM"GSAVE PROGRAM"
```

Graphic Utilities Source Code Listings

```
00001 ; GLOAD -- Save graphics display to disk
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; TRSDOS SVC Equates
00014
00015 @FSPEC: EQU 78 ;Test a filespec
00016 @OPEN: EQU 59 ;Open an existing file
00017 @READ: EQU 67 ;Read a record
00018 @CLOSE: EQU 60 ;Close a file
00019 @ERROR: EQU 26 ;Display an error message
00020 @DSPLY: EQU 10 ;Display a message
00021
00022 ; Port Equates
00023
00024 X: EQU 80H
00025 Y: EQU 81H
00026 DATA: EQU 82H
00027 STATUS: EQU 83H
00028
00029 ; Main Program
00030
00031 GLOAD: PUSH HL ;Save pointer from command line
00032
00033 LD A,10H
00034 OUT (236),A ;Turn on CRTC ports
00035 LD BC,1088H ;Load 16 Regs and point to control port
00036 LD HL,CRTC+15 ;Load backwards
00037
00038 ; This code programs the CRTC Chip for 80 x 24 screen
00039 ; Only required for Model III Graphics Boards
00040
00041 FDIV: OUT (C),B ;Select Data Register in CRTC
00042 LD A,(HL) ;Get the data
00043 OUT (137),A ;Store that in the CRTC
00044 DEC HL ;Move to previous entry
00045 DJNZ FDIV ;Decrement counter
00046
00047 LD HL,FCB ;Point at the FCB
00048 LD (HL),00H ;Zero the buffer
00049 LD DE,HL ;Build destination pointer
00050 INC DE ;Copy first byte to second position
00051 LD BC,32
00052 LDIR
00053
00054 POP HL
00055 LD A,00H
00056 CP (HL)
```

Graphics Utilities

```

00057      JR      Z,ERROR
00058      LD      DE,FCB
00059      TRSDOS  @FSPEC      ;Move filspec to FCB and do a syntax check
00060      JR      NZ,BOMB
00061
00062      LD      HL,BUFFER
00063      LD      DE,FCB
00064      LD      B,0
00065      TRSDOS  @OPEN      ;Open file if it exists, else create one
00066      JR      NZ,BOMB
00067
00068      LD      A,0B3H      ;status = inc X after write
00069      OUT     (STATUS),A
00070      XOR     A
00071      OUT     (X),A      ;init X & Y to zero
00072      OUT     (Y),A
00073      LD      E,A      ;counter for X values
00074      LD      D,80      ;80 X values
00075      LD      B,75      ;75 disk records for entire screen
00076  NXTREC:  PUSH    DE
00077      LD      DE,FCB
00078      TRSDOS  @READ      ;Read a record from disk
00079      POP     DE
00080      JR      NZ,BOMB
00081      LD      HL,BUFFER
00082      LD      C,B
00083      LD      B,0      ;256 bytes per record
00084  NGRPH:   LD      A,(HL)
00085      OUT     (DATA),A
00086      INC     HL
00087      INC     E
00088      LD      A,E
00089      CP      D
00090      JR      NZ,EGRPH   ;Same row?
00091      XOR     A
00092      LD      E,A
00093      OUT     (X),A      ;Next row. Set X to zero
00094      LD      A,(YPOS)
00095      INC     A
00096      LD      (YPOS),A
00097      OUT     (Y),A
00098  EGRPH:   DJNZ    NGRPH   ;Go get next graphics byte
00099      LD      B,C
00100      DJNZ    NXTREC      ;Go read next disk record
00101
00102  EXIT:    LD      DE,FCB
00103      TRSDOS  @CLOSE
00104      LD      A,0FCH      ;Status = graphics off, no waits, no incs.
00105      OUT     (STATUS),A
00106      LD      A,(EFLAG)
00107      LD      L,A
00108      LD      H,0
00109      CP      H
00110      RET     ;Return to TRSDOS or BASIC
00111
00112  ;      Error exits
00113
00114  ERROR:   LD      HL,PARM      ;Complain
00115      TRSDOS  @DSPLY
00116      JR      EXIT

```

Model 4 Computer Graphics

```
00117
00118 BOMB: LD (EFLAG),A
00119 OR 0C0H
00120 LD C,A
00121 TRSDOS @ERROR ;Display error message
00122 JR EXIT
00123
00124 PARM: DEFM 'Filespec required~'
00125 EFLAG: DEFB 0
00126 YPOS: DEFB 0
00127 FCB: DEFS 32
00128 BUFFER: DEFS 256
00129
00130 CRTC: DEFB 99,80,85,8,25,4,24,0,9,0,0,0,0,0
00131
00132 END GLOAD
```

Graphics Utilities

```

00001 ; GSAVE -- Save graphics display to disk
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; TRSDOS SVC Equates
00014
00015 @FSPEC: EQU 78 ;Test a filespec
00016 @INIT: EQU 58 ;Open an existing file, or create a new one
00017 @WRITE: EQU 75 ;Write a record
00018 @CLOSE: EQU 60 ;Close a file
00019 @ERROR: EQU 26 ;Display an error message
00020 @DSPLY: EQU 10 ;Display a message
00021
00022 ; Port Equates
00023
00024 X: EQU 80H
00025 Y: EQU 81H
00026 DATA: EQU 82H
00027 STATUS: EQU 83H
00028
00029 ; Main Program
00030
00031 GSAVE: PUSH HL ;Save pointer from command line
00032
00033 LD A,10H
00034 OUT (236),A ;Turn on CRTC ports
00035 LD BC,1088H ;Load 16 Regs and point to control port
00036 LD HL,CRTC+15 ;Load backwards
00037
00038 ; This code programs the CRTC Chip for 80 x 24 screen
00039 ; Only required for Model III Graphics Boards
00040
00041 FDIV: OUT (C),B ;Select Data Register in CRTC
00042 LD A,(HL) ;Get the data
00043 OUT (137),A ;Store that in the CRTC
00044 DEC HL ;Move to previous entry
00045 DJNZ FDIV ;Decrement counter
00046
00047 LD HL,FCB ;Point at the FCB
00048 LD (HL),00H ;Zero the buffer
00049 LD DE,HL ;Build destination pointer
00050 INC DE ;Copy first byte to second position
00051 LD BC,32
00052 LDIR
00053
00054 POP HL
00055 LD A,00H
00056 CP (HL)
00057 JR Z,ERROR
00058 LD DE,FCB
00059 TRSDOS @FSPEC ;Move filespec to FCB and do a syntax check
00060 JR NZ,BOMB

```

Model 4 Computer Graphics

```

00061
00062      LD      HL,BUFFER
00063      LD      DE,FCB
00064      LD      B,0
00065      TRSDOS  @INIT      ;Open file if it exists, else create one
00066      JR      NZ,BOMB
00067
00068      LD      A,DE3H      ;status = inc X after read
00069      OUT     (STATUS),A
00070      XOR     A
00071      OUT     (X),A        ;init X & Y to zero
00072      OUT     (Y),A
00073      LD      E,A        ;counter for X values
00074      LD      D,80        ;80 X values
00075      LD      B,75        ;75 disk records for entire screen
00076      NXTREC: LD      HL,BUFFER
00077      LD      C,B
00078      LD      B,0        ;256 bytes per record
00079      NGRPH:  IN      A,(DATA) ;Get next graphics byte
00080      LD      (HL),A      ; and put in buffer
00081      INC     HL
00082      INC     E
00083      LD      A,E
00084      CP      D
00085      JR      NZ,EGRPH    ;Same row?
00086      XOR     A
00087      LD      E,A
00088      OUT     (X),A        ;Next row. Set X to zero
00089      LD      A,(YPOS)
00090      INC     A
00091      LD      (YPOS),A
00092      OUT     (Y),A
00093      EGRPH:  DJNZ    NGRPH ;Go get next graphics byte
00094      PUSH    DE
00095      LD      DE,FCB
00096      TRSDOS  @WRITE      ;Write a record to disk
00097      POP     DE
00098      JR      NZ,BOMB
00099      LD      B,C
00100      DJNZ    NXTREC      ;Go fill buffer for next record
00101
00102      EXIT:   LD      DE,FCB
00103      TRSDOS  @CLOSE
00104      LD      A,@FCH
00105      OUT     (STATUS),A   ;Status = graphics off, no waits, no incs.
00106      LD      A,(EFLAG)
00107      LD      L,A
00108      LD      H,0
00109      OR      A            ;Test Error byte
00110      RET          ;Return to TRSDOS or BASIC
00111
00112      ;      Error exits
00113
00114      ERROR:  LD      HL,PARM ;Complain
00115      TRSDOS  @DSPLY
00116      JR      EXIT
00117
00118      BOMB:   LD      (EFLAG),A
00119      OR      @COH
00120      LD      C,A

```

Graphics Utilities

```
00121      TRSDOS  @ERROR      ;Display error message
00122      JR      EXIT
00123
00124      PARM:    DEFM      'Filespec required~'
00125      EFLAG:   DEFB      0
00126      YPOS:    DEFB      0
00127      FCB:     DEFS      32
00128      BUFFER:  DEFS      256
00129
00130      CRTC:     DEFB      99,80,85,8,25,4,24,0,9,0,0,0,0,0
00131
00132      END      GSAVE
```

Model 4 Computer Graphics

```
00001 ; GRON -- Turn on graphics display with waits on
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; Port Equates
00014
00015 STATUS: EQU 83H
00016
00017 ; Main Program
00018
00019 GRON: LD A,10H
00020 OUT (236),A ;Turn on CRTC ports
00021 LD BC,1080H ;Load 16 Regs and point to control port
00022 LD HL,CRTC+15 ;Load backwards
00023
00024 ; This code programs the CRTC Chip for 80 x 24 screen
00025 ; Only required for Model III Graphics Boards
00026
00027 FDIV: OUT (C),B ;Select Data Register in CRTC
00028 LD A,(HL) ;Get the data
00029 OUT (137),A ;Store that in the CRTC
00030 DEC HL ;Move to previous entry
00031 DJNZ FDIV ;Decrement counter
00032
00033 LD A,0FFH
00034 OUT (STATUS),A
00035 XOR A
00036 LD HL,0
00037 RET ;Return to TRSDOS or BASIC
00038
00039 CRTC: DEFB 99,80,85,8,25,4,24,0,9,0,0,0,0,0
00040
00041 END GRON
```

Graphics Utilities

```

00001 ; GPRINT -- Print graphics screen to graphics printer
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; TRSDOS SVC Equates
00014
00015 @PRT: EQU 6 ;Print a character on the printer
00016 @PRINT: EQU 14 ;Print a line on the printer
00017 @FLAGS: EQU 101 ;Point to system control flags
00018
00019 ; Port Equates
00020
00021 X: EQU 80H
00022 Y: EQU 81H
00023 DATA: EQU 82H
00024 STATUS: EQU 83H
00025
00026 ; Main Program
00027
00028 GPRINT: LD A,10H
00029 OUT (236),A ;Turn on CRTC ports
00030 LD BC,15
00031 LD HL,CRTC
00032
00033 ; This code programs the CRTC Chip for 80 x 24 screen
00034 ; Only required for Model III Graphics Boards
00035
00036 FDIV: LD A,B ;Program CRTC chip for 80 by 24
00037 OUT (136),A
00038 LD A,(HL)
00039 OUT (137),A
00040 INC HL
00041 INC B
00042 LD A,B
00043 CP C
00044 JR NZ,FDIV
00045
00046 LD A,00BH ;Output a Control byte to cause
00047 OUT (STATUS),A ; Y to automatically dec. on a read
00048
00049 CALL INITBF ;Zero print buffer
00050
00051 XOR A ;Set A to 0
00052 OUT (X),A ;Initialize the X position
00053 LD (BPOS),A ; " " bit position
00054 LD (XLOC),A ; " " location counter
00055
00056 ; Set the printer to start graphics mode
00057
00058 LD C,12H ;Begin Graphics mode
00059 TRSDOS @PRT ;Output Character
00060 JP NZ,BOMB ;Printer Not Ready

```

Model 4 Computer Graphics

```

00061
00062 ;      Turn off international character set translation
00063
00064 TRSDOS  @FLAGS
00065 LD      A,(IY+8)      ;Get IFLAGS
00066 LD      (OLD),A      ;Save a copy of the current settings
00067 RES     6,(IY+8)      ;Turn off bit 6 (Intl. Translation)
00068
00069 FDIV1: LD      IX,BUFFER      ;point IX at the printer buffer
00070 LD      B,240          ;go through a whole column of bytes
00071 LD      A,B           ;Put value in A and decrement
00072 DEC     A            ; so it can be put out as
00073 OUT     (Y),A         ; the Y position
00074 COLUMN: LD     HL,MASK      ;Point at character mask
00075 IN      A,(DATA)      ;input a graphics byte
00076 AND     (HL)          ;chop off all but proper bit
00077 CALL    PO,SET0       ;if result is odd parity set bit 0
00078 ; otherwise bit A is 0
00079 LD      HL,BPOS       ;point HL at the bit position
00080 PUSH    BC           ;save register B (for DJNZ loop)
00081 LD      B,(HL)        ;get count
00082 INC     B            ;increment (in case it is 0)
00083 DECJ:  DEC     B       ;move bit left BPOS number of times
00084 JR      Z,PAST       ;if done, move on...
00085 RLC     A            ;move bit left one position
00086 JR      DECJ         ;repeat loop
00087 PAST:  POP     BC     ;get loop counter back
00088 OR      (IX)         ;merge A with byte of printer buffer
00089 LD      (IX),A       ;put merged result in buffer
00090 INC     IX          ;increment buffer pointer
00091 DJNZ   COLUMN      ;continue loop
00092
00093 LD      A,7          ;See if BPOS has gotten to 8.
00094 INC     (HL)         ; If it has (printer uses 7 bits)
00095 CP      (HL)         ; print the buffer and reset
00096 CALL    Z,PRNDRS    ; BPOS to 0
00097
00098 LD      HL,MASK      ;After getting a vertical row of bits
00099 RRC     (HL)         ; rotate the mask right one position
00100 LD      A,80H        ;Check to see if its back to
00101 CP      (HL)         ; it's original value, if not
00102 JR      NZ,FDIV1     ; go get another row of bits
00103 LD      A,(XLOC)     ;If so, get X pos (to increment it)
00104 CP      79          ;Check to see if we are at the end...
00105 JP      Z,BYE
00106 INC     A            ;otherwise increment the X counter
00107 LD      (XLOC),A     ;and store it back
00108 OUT     (X),A        ;also update the port value
00109 JR      FDIV1       ;now go get another row of bits
00110
00111 SET0:  LD      A,1     ;set A to binary 0000 0001
00112 RET                     ; and return
00113
00114 ;      This routine edits the print buffer to remove trailing blanks
00115 ;      and then sends the data to the printer
00116
00117 PRNDRS: LD     HL,BUFFER+239 ;Set up the
00118 LD      D,00H          ;Print terminator
00119 LD      B,239          ;Start testing
00120 LD      A,80H          ;Test against nothing

```

Graphics Utilities

```

00121  CLEAN:  CP      (HL)          ;Anything there?
00122          JR      NZ,STOP      ;Found something to print
00123          LD      (HL),D        ;Then get rid of it
00124          DEC      HL
00125          DJNZ     CLEAN         ;Shorten the line as much as possible
00126  STOP:   LD      HL,BUFFER      ;Point to the start of the text
00127          TRSDOS  @PRINT         ;Print the contents of BUFFER and do a C/R
00128          XOR      A             ;clear A
00129          LD      (BPOS),A        ;reset bit position counter
00130
00131  ;      Initialize the Printer Buffer
00132
00133  INITBF:  LD      HL,BUFFER      ;Point at the buffer
00134          LD      (HL),80H        ;Fill the buffer with x'80'
00135          LD      DE,HL           ;Build destination pointer
00136          INC      DE             ;Copy first byte to second position
00137          LD      BC,239          ;Zero 240 bytes
00138          LDIR
00139          RET
00140
00141  BYE:     CALL     PRNDRS
00142          LD      C,1EH           ;End Graphics Print Mode
00143          TRSDOS  @PRT
00144
00145  BOMB:    LD      A,0FCH          ;Status = graphics off, no waits, no incs
00146          OUT     (STATUS),A
00147
00148          TRSDOS  @FLAGS          ;Point to system flags again
00149          LD      A,(OLD)         ;Get old contents of IFLAG$
00150          LD      (IY+8),A        ;Set things back the way they were
00151
00152          LD      HL,0            ;Zero Return Code
00153          RET                    ;Return to TRSDOS or BASIC
00154
00155
00156  MASK:    DEFB     80H           ;Mask to use in extracting bits
00157  BUFFER:  DEFB     240          ;Printer data buffer
00158          DEFB     0DH           ;Terminator for Print Line
00159  BPOS:    DEFB     0            ;Bit position in printer buffer
00160  XLOC:    DEFB     0            ;Current X location value
00161  OLD:     DEFB     0            ;Old contents of IFLAG$
00162
00163  CRTC:    DEFB     99,80,85,8,25,4,24,24,0,9,0,0,0,0,0
00164
00165          END      GPRINT

```

Model 4 Computer Graphics

```

00001 ; GCLS -- Clear graphics screen
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; Port Equates
00014
00015 X: EQU 80H
00016 Y: EQU 81H
00017 DATA: EQU 82H
00018 STATUS: EQU 83H
00019
00020 INCY: EQU 70H
00021 INCXY: EQU 30H
00022
00023 ; Main Program
00024
00025 GCLS: LD A,10H
00026 OUT (236),A ;Turn on CRTC ports
00027 LD BC,1088H ;Load 16 Regs and point to control port
00028 LD HL,CRTC+15 ;Load backwards
00029
00030 ; This code programs the CRTC Chip for 80 x 24 screen
00031 ; Only required for Model III Graphics Boards
00032
00033 FDIV: OUT (C),B ;Select Data Register in CRTC
00034 LD A,(HL) ;Get the data
00035 OUT (137),A ;Store that in the CRTC
00036 DEC HL ;Move to previous entry
00037 DJNZ FDIV ;Decrement counter
00038
00039 LD A,INCY ;Set graphics status:
00040 OUT (STATUS),A ; Graphics off, waits off, inc Y
00041 XOR A
00042 OUT (X),A ;Set X & Y address to 0
00043 OUT (Y),A
00044 LD B,80 ;80 X addresses
00045 OUTER: LD C,B
00046 LD B,239 ;239 Y addresses. 240th done after loop.
00047 INNER: OUT (DATA),A ;Zero graphics memory
00048 DJNZ INNER ;Go clear next Y
00049 LD A,INCXY ;Set status to inc X & Y after write
00050 OUT (STATUS),A
00051 XOR A
00052 OUT (DATA),A ;and clear last (240th) Y address
00053 OUT (Y),A ;Set Y back to zero
00054 LD A,INCY ;Reset status to inc Y only
00055 OUT (STATUS),A
00056 XOR A
00057 LD B,C
00058 DJNZ OUTER ;Go clear next X
00059 LD A,0FCH ;Set status: graphics off, no waits, no incs
00060 OUT (STATUS),A

```

Graphics Utilities

```
00061
00062      XOR      A
00063      LD       HL,0
00064      RET                               ;Return to BASIC or TRSDOS
00065
00066  CRTC:  DEFB    99,80,85,8,25,4,24,24,0,9,0,0,0,0,0
00067
00068      END      GCLS
```

Model 4 Computer Graphics

```
00001 ; GROFF -- Turn graphics display off with waits off
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; Port Equates
00014
00015 STATUS: EQU 83H
00016
00017 ; Main Program
00018
00019 GROFF: LD A,10H
00020 OUT (236),A ;Turn on CRTC ports
00021 LD BC,1088H ;Load 16 Regs and point to control port
00022 LD HL,CRTC+15 ;Load backwards
00023
00024 ; This code programs the CRTC Chip for 80 x 24 screen
00025 ; Only required for Model III Graphics Boards
00026
00027 FDIV: OUT (C),B ;Select Data Register in CRTC
00028 LD A,(HL) ;Get the data
00029 OUT (137),A ;Store that in the CRTC
00030 DEC HL ;Move to previous entry
00031 DJNZ FDIV ;Decrement counter
00032
00033 LD A,0FCH
00034 OUT (STATUS),A
00035 XOR A
00036 LD HL,0
00037 RET ;Return to TRSDOS or BASIC
00038
00039 CRTC: DEFB 99,80,85,8,25,4,24,0,9,0,0,0,0,0,0
00040
00041 END GROFF
```


Graphics Utilities

```

00001 ; GPRT2 -- Print graphics X horizontal
00002
00003         PSECT    2600H           ;Model 4 Overlay area
00004         PRINT    SHORT,NOMAC
00005
00006 ;         Macros
00007
00008 TRSDOS: MACRO    #1
00009         LD        A,#1
00010         RST       28H
00011         ENDM
00012
00013 ;         TRSDOS SVC Equates
00014
00015 @PRT: EQU        6                ;Print a character on the printer
00016 @PRINT: EQU      14              ;Print a line on the printer
00017 @FLAGS: EQU      101             ;Point to system control flags
00018
00019 ;         Port Equates
00020
00021 X: EQU          80H
00022 Y: EQU          81H
00023 DATA: EQU      82H
00024 STATUS: EQU     83H
00025
00026 ;         Main Program
00027
00028 GPRT2: LD        A,10H
00029         OUT       (236),A         ;Turn on CRTC ports
00030         LD        BC,1088H       ;Load 16 Regs and point to control port
00031         LD        HL,CRTC+15     ;Load backwards
00032
00033 ;         This code programs the CRTC Chip for 80 x 24 screen
00034 ;         Only required for Model III Graphics Boards
00035
00036 FDIV: OUT       (C),B           ;Select Data Register in CRTC
00037         LD        A,(HL)         ;Get the data
00038         OUT       (137),A        ;Store that in the CRTC
00039         DEC       HL             ;Move to previous entry
00040         DJNZ      FDIV           ;Decrement counter
00041
00042 ;         Set the printer to start graphics mode
00043
00044         LD        C,12H          ;Begin Graphics mode
00045         TRSDOS    @PRT           ;Output Character
00046         JR        NZ,BOMB        ;Printer Not Ready
00047
00048 ;         Turn off international character set translation
00049
00050         TRSDOS    @FLAGS
00051         LD        A,(1Y+8)       ;Get IFLAG$
00052         LD        (OLD),A        ;Save a copy of the current settings
00053         RES       6,(1Y+8)       ;Turn off bit 6 (Intl. Translation)
00054
00055 ;         Open Video Memory
00056
00057         LD        C,0            ;Graphics Y address
00058         LD        A,0E3H         ;Open RAM with video waits
00059         OUT       (STATUS),A
00060

```

Model 4 Computer Graphics

```

00061      ;      Initialize the Printer Buffer
00062
00063      NEWLN:  PUSH    BC              ;Save BC
00064              LD      HL,BUFFER      ;Point at the buffer
00065              LD      (HL),80H        ;Fill the buffer with x'80'
00066              LD      DE,HL          ;Build destination pointer
00067              INC      DE              ;Copy first byte to second position
00068              LD      BC,639          ;Zero 640 bytes
00069              LDIR
00070              POP      BC              ;Restore BC
00071
00072              LD      D,1              ;Bit in buf to set
00073
00074      NEWRW:  LD      A,C
00075              OUT      (Y),A          ;Update Y address
00076              INC      C
00077              LD      HL,BUFFER
00078              XOR      A
00079              OUT      (X),A          ;Restart X address
00080              LD      B,80            ;Get 80 graphics bytes
00081
00082              PUSH    BC              ;Save Y & loop counter
00083      BYTE1:  IN      A,(DATA)
00084              LD      C,A              ;Save graphics byte in C
00085              LD      E,80H          ;Get bits left to right
00086      BIT:    LD      A,C
00087              AND      E
00088              JR      Z,OFF
00089              LD      A,D
00090              OR      (HL)
00091              LD      (HL),A          ;Set bit in buffer
00092      OFF:    INC      HL              ;Next buffer byte
00093              SRL      E              ;Next bit
00094              JR      NZ,BIT
00095              DJNZ    BYTE1
00096              POP     BC
00097
00098              LD      A,240
00099              CP      C              ;Last Y address?
00100              JR      Z,DONE
00101              SLA      D              ;Next bit in buffer
00102              JP      P,NEWRW
00103
00104              CALL    PRINT           ;Print buffer
00105              JR      NZ,BOMB          ;An error occurred.
00106              JR      NEWLN
00107
00108      DONE:   CALL    PRINT
00109
00110      BOMB:   LD      C,1EH           ;End Graphics Print Mode
00111              TRSDOS  @PRT           ;We do not care if this one fails.
00112
00113              LD      A,@FCH          ;Status = graphics off, no waits, no incs
00114              OUT      (STATUS),A
00115
00116              TRSDOS  @FLAGS          ;Point to system flags again
00117              LD      A,(OLD)          ;Get old contents of IFLAG$
00118              LD      (IY+8),A         ;Set things back the way they were
00119
00120              LD      HL,0             ;Zero Return Code

```

Graphics Utilities

```

00121          RET                      ;Return to TRSDOS or BASIC
00122
00123 PRINT:    PUSH    BC
00124          LD      HL,BUFFER+639      ;Point to the end of the buffer
00125          LD      D,0DH              ;Key on the terminator
00126          LD      BC,640             ;Set counter
00127 PFDIV:     LD      A,(HL)           ;Look at a byte
00128          CP      80H               ;Is it a nothing?
00129          JR      NZ,STOP            ;Then stop
00130          DEC     BC                ;Decrement counter
00131          DEC     HL                ;Decrement pointer
00132          LD      A,B               ;See if we are done
00133          OR      C                 ;Well?
00134          JR      NZ,PFDIV          ;Loop for more
00135 STOP:      INC     HL              ;Move pointer back one
00136          LD      (HL),0DH          ;Load a terminator after last valid byte
00137          LD      HL,BUFFER         ;Point at the text to be printed
00138          TRSDOS @PRINT             ;Display it
00139          POP     BC
00140          RET                      ;Done, exit
00141
00142 CRTC:      DEFB     99,80,85,8,25,4,24,24,0,9,0,0,0,0,0,0
00143
00144 OLD:       DEFB     0               ;Old contents of IFLAG$
00145 BUFFER:    DEFS     640
00146          DEFB     0DH              ;Carriage return
00147
00148          END      GPRT2

```

Model 4 Computer Graphics

```

00001 ; GPRT3 -- Print graphics X horizontal double Y axis
00002
00003 PSECT 2600H ;Model 4 Overlay area
00004 PRINT SHORT,NOMAC
00005
00006 ; Macros
00007
00008 TRSDOS: MACRO #1
00009 LD A,#1
00010 RST 28H
00011 ENDM
00012
00013 ; TRSDOS SVC Equates
00014
00015 @PRT: EQU 6 ;Print a character on the printer
00016 @PRINT: EQU 14 ;Print a line on the printer
00017 @FLAGS: EQU 101 ;Point to system control flags
00018
00019 ; Port Equates
00020
00021 X: EQU 80H
00022 Y: EQU 81H
00023 DATA: EQU 82H
00024 STATUS: EQU 83H
00025
00026 ; Main Program
00027
00028 GPRT3: LD A,10H
00029 OUT (236),A ;Turn on CRTC ports
00030 LD BC,1088H ;Load 16 Regs and point to control port
00031 LD HL,CRTC+15 ;Load backwards
00032
00033 ; This code programs the CRTC Chip for 80 x 24 screen
00034 ; Only required for Model III Graphics Boards
00035
00036 FDIV: OUT (C),B ;Select Data Register in CRTC
00037 LD A,(HL) ;Get the data
00038 OUT (137),A ;Store that in the CRTC
00039 DEC HL ;Move to previous entry
00040 DJNZ FDIV ;Decrement counter
00041
00042 ; Set the printer to start graphics mode
00043
00044 LD C,12H ;Begin Graphics mode
00045 TRSDOS @PRT ;Output Character
00046 JR NZ,80MB ;Printer Not Ready
00047
00048 ; Turn off international character set translation
00049
00050 TRSDOS @FLAGS
00051 LD A,(1Y+8) ;Get IFLAG$
00052 LD (OLD),A ;Save a copy of the current settings
00053 RES 6,(1Y+8) ;Turn off bit 6 (Intl. Translation)
00054
00055 ; Open Video Memory
00056
00057 LD C,0 ;Graphics Y address
00058 LD A,0E3H ;Open RAM with video waits
00059 OUT (STATUS),A
00060

```

Graphics Utilities

```

00061 ;           Initialize the Printer Buffer
00062
00063         LD      D,3           ;Bit(s) in buf to set
00064
00065 NEWLN:  PUSH    BC           ;Save BC
00066         PUSH    DE
00067         LD      HL,BUFFER     ;Point at the buffer
00068         LD      (HL),80H      ;Fill the buffer with x'80'
00069         LD      DE,HL         ;Build destination pointer
00070         INC      DE           ;Copy first byte to second position
00071         LD      BC,639       ;Zero 640 bytes
00072         LDIR
00073         POP      DE
00074         POP      BC           ;Restore BC
00075
00076 NEWRW:  LD      A,C
00077         OUT      (Y),A        ;Update Y address
00078         LD      A,40H
00079         CP      D
00080         JR      Z,NEWR1      ;If printing row second time
00081         INC      C           ;           Move to next row
00082 NEWR1:  LD      HL,BUFFER
00083         XOR      A
00084         OUT      (X),A        ;Restart X address
00085         LD      B,80         ;Get 80 graphics bytes
00086         LD      A,4
00087         CP      D
00088         JR      NZ,BYTE
00089         LD      D,6
00090
00091 BYTE:   PUSH    BC           ;Save Y & loop counter
00092 BYTE1:  IN      A,(DATA)
00093         LD      C,A          ;Save graphics byte in C
00094         LD      E,80H        ;Get bits left to right
00095 BIT:    LD      A,C
00096         AND      E
00097         JR      Z,OFF
00098         LD      A,D
00099         OR      (HL)
00100        LD      (HL),A        ;Set bit in buffer
00101 OFF:    INC      HL          ;Next buffer byte
00102         SRL      E           ;Next bit
00103         JR      NZ,BIT
00104         DJNZ    BYTE1
00105         POP      BC
00106
00107         LD      A,240
00108         CP      C           ;Last Y address?
00109         JR      Z,DONE
00110         SLA      D           ;Next bit in buffer
00111         SLA      D
00112         JR      Z,ENDRW
00113         JP      P,NEWRW
00114         LD      A,7FH
00115         AND      D
00116         LD      D,A
00117         JR      NZ,NEWRW
00118         LD      D,3
00119         JR      ENDR2
00120

```

Model 4 Computer Graphics

```

00121 ENDRW: LD      D,1
00122 ENDR2: PUSH    DE
00123        CALL    PRINT          ;Print buffer
00124        POP      DE
00125        JR       NZ,BOMB        ;Printer Error
00126        JR       NEWLN
00127
00128 DONE:   CALL    PRINT
00129
00130 BOMB:    LD      C,1EH          ;End Graphics Print Mode
00131        TRSDOS   @PRT          ;We do not care if this one fails.
00132
00133        LD      A,DFCH          ;Status = graphics off, no waits, no incs
00134        OUT     (STATUS),A
00135
00136        TRSDOS   @FLAGS        ;Point to system flags again
00137        LD      A,(OLD)        ;Get old contents of IFLAG$
00138        LD      (IY+8),A       ;Set things back the way they were
00139
00140        LD      HL,0           ;Zero Return Code
00141        RET                     ;Return to TRSDOS or BASIC
00142
00143 PRINT:    PUSH    BC
00144        LD      HL,BUFFER+639  ;Point to the end of the buffer
00145        LD      D,0DH          ;Key on the terminator
00146        LD      BC,640         ;Set counter
00147 PFDIV:    LD      A,(HL)       ;Look at a byte
00148        CP      80H           ;Is it a nothing?
00149        JR      NZ,STOP        ;Then stop
00150        DEC     BC             ;Decrement counter
00151        DEC     HL             ;Decrement pointer
00152        LD      A,B           ;See if we are done
00153        OR      C              ;Well?
00154        JR      NZ,PFDIV       ;Loop for more
00155 STOP:     INC      HL          ;Move pointer back one
00156        LD      (HL),0DH       ;Load a terminator after last valid byte
00157        LD      HL,BUFFER      ;Point at the text to be printed
00158        TRSDOS   @PRINT        ;Display it
00159        POP      BC
00160        RET                     ;Done, exit
00161
00162 CRTC:     DEFB     99,80,85,8,25,4,24,24,0,9,0,0,0,0,0
00163
00164 OLD:      DEFB     0           ;Old contents of IFLAG$
00165 BUFFER:   DEFS     640
00166          DEFB     0DH          ;Carriage return
00167
00168          END      GPRT3

```

4/ Graphics Subroutine Library (FORTRAN)

The Graphics Subroutine Library included on the Computer Graphics diskette lets you use the functions of TRS-80 Computer Graphics while programming in Model 4 FORTRAN (26-2219). This library (GRPLIB/REL) must be linked to any FORTRAN program that accesses the Graphics Subroutines.

BASICG vs. the Graphics Subroutine Library

The Graphics Subroutine Library contains subroutines which provide the same capabilities as the Graphics commands and functions in BASICG. The Graphics subroutines have basically the same names and parameters as the BASICG commands. The major differences between the Library subroutines and the BASICG commands are:

- The BASICG command LINE has three corresponding library subroutines: LINE, LINEB, and LINEBF. LINEB and LINEBF provide the functions of the BASICG command LINE with the parameters B and BF respectively.
- The BASICG command PAINT has two corresponding library subroutines: PAINT and PAINTT. PAINT is for painting solid black or white, and PAINTT is for painting with tiling.
- The Library subroutines that correspond to BASICG commands that use (x,y) coordinates (except for VIEW) use (x,y) coordinates that have been previously set. The subroutines used to set the coordinates are SETXY and SETXYR.

Setting Points using SETXY and SETXYR

The coordinates specified by SETXY or SETXYR will be called the "current" and "previous" coordinates. Subroutines that use one (x,y) coordinate pair use the "current" coordinates and subroutines that use two (x,y) pairs use both the "current" and the "previous" coordinates. Each call to SETXY or SETXYR sets the coordinates as follows:

1. Assign the values of the "current" (x,y) coordinates to the "previous" (x,y) coordinates, (discarding the old "previous" coordinates).
2. Assign new values for the "current" (x,y) coordinates as specified by the arguments supplied. SETXY simply sets the "current" coordinates to the values of its arguments. SETXYR adds the values of its arguments to the "current" coordinates to obtain the new coordinates.

Initialization

Before any calls are made to Graphics, the Graphics library and board must be initialized. A special initialization routine (GRPINI) is included in the library. A call to GRPINI must be made as the first access to the Graphics library.

Example

```
00100  C  SAMPLE INITIALIZATION
00150      DIMENSION V(30,30)
00200      CALL GRPINI (0)
```

Linking

The Library (GRPLIB/REL) must be linked to any programs that access the Graphics Subroutines. You must use the linker (L80) to generate the load module.

Example

```
L80 (ENTER)
*SAMPLE:1-N
*GRPHSAM,GRPLIB-S,FORLIB-S,-U
*-E
```

This example links both the Graphics Library and the FORTRAN Subroutine Library to the relocatable file GRPHSAM/REL. In this example, SAMPLE:1-N is the file name, drive specification, and switch, respectively; GRPHSAM, GRPLIB-S, FORLIB-S, and -U are the names of the relocatable modules to be linked and their respective switches. -E ends the routine and creates the executable program SAMPLE. The *'s in the example are prompts for the user — not data to be entered.

Note: If there are unresolved external references, the FORTRAN Library may need to be scanned a second time.

Errors

If you enter incorrect parameters for any of the Graphics Subroutines, your screen will display:

```
GRAPHICS ERROR
```

and return program control to TRSDOS Ready. This is the only error message you'll get when executing the Subroutines.

Important Note: Free memory is utilized by the Graphic Routine for temporary storage. Extreme care should be exercised if your program accesses this memory.

Routines/Functions

Most of the FORTRAN Subroutines and functions described in this section have a corresponding command in the **Graphics BASIC Language Reference** section of this manual.

Graphics Subroutine Library (FORTRAN)

FORTRAN Routines	
Routine	Action
CIRCLE	Draws a circle, arc, semicircle, or ellipse.
CLS	Clears the Graphics Screen.
GET	Reads the contents of a rectangular pixel area into an array.
GPRINT	Displays textual data on the Graphics Screen.
GRPINI	Graphics initialization routine.
LINE	Draws a line.
LINEB	Draws a box.
LINEBF	Draws a filled box.
LOCATE	Sets the direction for displaying textual data on the Graphics Screen.
PAINT	Paints the screen in specified OFF/ON color.
PAINTT	Paints the screen in a specified pattern.
PRESET	Sets pixel OFF/ON.
PSET	Sets pixel OFF/ON.
PUT	Puts the stored array on the screen.
SCREEN	Selects the screen.
SETXY	Sets (x,y) coordinates (absolute).
SETXYR	Sets (x,y) coordinates (relative).
VIEW	Sets up a viewport where graphics is displayed.

Table 7

FORTRAN Functions	
Function	Action
POINT	Reads a pixel's value at a specified coordinate.
FVIEW	Reads a viewport's parameters.

Table 8

CIRCLE

Draws a Circle, Arc, Semicircle, Point or Ellipse

CIRCLE (*radius,color,start,end,ar*)

radius is of INTEGER type and specifies the radius of the circle.

color is of LOGICAL type, specifies the OFF/ON color of the border of the circle and is an integer expression of either 0 or 1.

start is of REAL type and specifies the startpoint of the circle.

end is of REAL type and specifies the endpoint of the circle.

ar is the aspect ratio, is of REAL type and determines the major axis of the circle. If *ar* is 0, 0.5 is used.

CIRCLE draws a circle. By varying *start*, *end*, and aspect ratio, you can draw arcs, semicircles, or ellipses using current X- and Y-coordinates as the centerpoint (set by SETXY or SETXYR).

If *start* and *end* are 0.0, a circle is drawn starting from the center right side of the circle. Note: In the CIRCLE statement, *end* is read as $2 \times \text{PI}$ even though you have entered 0.0. If you enter 0.0 for aspect ratio, a symmetric circle is drawn.

Example

```
CALL CIRCLE(100,1,0.0,0.0,0.0)
```

Sample Program

This example draws and paints a circle.

```
00010  C    SAMPLE PROGRAM FOR CIRCLE
00020      LOGICAL COLOR,OPTION
00030      COLOR=1
00040      OPTION=0
00050      CALL GRPINI(OPTION)
00060      CALL CLS
00070      CALL SETXY(300,100)
00080      CALL CIRCLE(100,COLOR,0.0,0.0,0.0)
00090      CALL PAINT(COLOR,COLOR)
00100      END
```

CLS

Clears Graphics Screen

CLS

Example

```
CALL CLS
```

Sample Program (see CIRCLE)

GET

Reads Contents of a Rectangular Pixel Area into an Array

GET (array,size)

array is any type and is the name of the array you specify.

size is of INTEGER type and specifies the size of the *array* in terms of bytes.

GET reads the contents of a rectangular pixel area into an *array* for future use by PUT. The pixel area is a group of pixels which are defined by the current *x* and *y*, and the previous *X*- and *Y*-coordinates specified by the SETXY call. The first two bytes of *array* are set to the horizontal (*X*-axis) number of pixels in the pixel area; the second two bytes are set to the vertical (*Y*-axis) number of pixels in the pixel area. The remainder of *array* represents the status of each pixel (either ON or OFF) in the pixel area. The data is stored in a row-by-row format. The data is stored eight pixels per byte and each row starts on a byte boundary.

Array Limits

When the *array* is defined, space is reserved in memory for each element of the *array*. The size of the *array* is limited by the amount of memory available for use by your program — each real number in your storage *array* uses four memory locations (bytes).

The *array* must be large enough to hold your graphic display and the rectangular area defined must include all the points you want to store.

To determine the minimum *array* size:

1. Divide the number of *X*-axis pixels by 8 and round up to the next higher integer.
2. Multiply the result by the number of *Y*-axis pixels.

When counting the *X*-*Y* axis pixels, be sure to include the first and last pixel.

3. Add four to the total.
4. Divide by four (for real numbers) and two (for integers) rounding up to the next higher integer. (Note: If you're using a LOGICAL *array*, the result of Step #3 above will produce the desired array size.)

When using *arrays* the position and size of the rectangular pixel area is determined by the current and previous (*x*,*y*) coordinates.

Position: upper left corner = startpoint = (*x*₁,*y*₁)
 lower left corner = endpoint = (*x*₂,*y*₂)

Size (in pixels): Width = *x*₂ - *x*₁ + 1
 length = *y*₂ - *y*₁ + 1

Example

```
CALL GET(A,4000)
```

Model 4 Computer Graphics

Sample Program

This example draws a circle, saves the circle into an *array*, then restores the *array* to the graphics video.

```
00050  C      SAMPLE FOR GET AND PUT
00100      LOGICAL V(128),ACTION
00150          ACTION=1
00200      CALL GRPINI(0)
00300      CALL CLS
00350  C      DRAW A CIRCLE
00400      CALL SETXY(30,30)
00500      CALL CIRCLE(10,1,0.0,0.0,0.0)
00550  C      SET COORDINATES FOR GET ARRAY
00600      CALL SETXY(10,10)
00700      CALL SETXY(40,40)
00750  C      STORE GRAPHICS INTO ARRAY WITH GET
00800      CALL GET(V,128)
00900      DO 10 I=1,5000
01000  10    CONTINUE
01050  C      CLEAR SCREEN AND RESTORE GRPH FROM ARRAY
01100      CALL CLS
01200      CALL SETXY(110,110)
01300      CALL PUT(V,ACTION)
01400      DO 20 I=1,5000
01500  20    CONTINUE
01600      END
```

GPRINT

Write Text Characters to the Graphics Screen

GPRINT (cnt,array)

cnt is of INTEGER type and specifies the number of characters to display.

array is a one dimensional LOGICAL array containing the characters to be displayed.

GPRINT is used to write text characters to the Graphics Screen. This is the easiest way to display textual data on the Graphics Screen. Characters are displayed starting at the current (x,y) coordinates and going in the direction specified by the most recently executed LOCATE call. If no LOCATE call was executed prior to the GPRINT call, a direction of 0 is assumed.

GPRINT will only print text characters (see the *Model 4 Disk System Owner's Manual*). Each character displayed in the 0 or 2 direction uses an 8 x 8 pixel grid; each character displayed in the 1 or 3 direction uses a 16 x 8 grid. Executing this command will set the current (x,y) coordinates to the end of the last character that was displayed.

Graphics Subroutine Library (FORTRAN)

Displaying text in the direction 0 engages a wraparound feature. If the end of a line is reached, the display will be continued on the next line. If the end of the screen is reached, the display will be continued at the beginning of the screen without scrolling. If there is not enough room to display at least one character at the current (x,y) coordinates, a GRAPHICS ERROR will result. When displaying text in other directions, an attempt to display text outside the currently defined screen will cause a GRAPHICS ERROR to be given.

GRPINI Graphics Initialization Routine

GRPINI(option)

option is of LOGICAL type; 0 clears the Graphics Screen, non-zero does not clear the Graphics Screen.

GRPINI is the graphics initialization routine. This function must be called before any other graphics calls are made in FORTRAN.

Example

```
CALL GRPINI(1)
```

Sample Program (see CIRCLE)

LINE Draws Line

LINE (color, style)

color is of LOGICAL type, specifies the OFF/ON color of a line and is an integer expression of either 0 (OFF, black) or 1 (ON, white).

style is of INTEGER type, specifies the pattern of the line and is a number in the integer range. -1 indicates a solid line.

LINE draws a line between the previous and current coordinates. These coordinates are set by the SETXY or SETXYR subroutines.

Example

```
CALL LINE (1,-1)
```

Model 4 Computer Graphics

Sample Program

This example draws a diagonal line connected to a box, which is connected to a filled box.

```
00010  C    SAMPLE FOR LINE LINEB LINEBF
00020      LOGICAL COLOR
00030      COLOR=1
00040      CALL GRPINI(0)
00050      CALL CLS
00060      CALL SETXY(1,1)
00070      CALL SETXY(210,80)
00080      CALL LINE(COLOR,-1)
00090      CALL SETXY(420,160)
00100  C    COORDINATES ARE NOW (210,80) (420,160)
00110      CALL LINEB(COLOR,-1)
00120      CALL SETXY(639,239)
00130  C    COORDINATES ARE NOW (420,160) (639,239)
00140      CALL LINEBF(COLOR)
00150      END
```

LINEB Draws Box

LINEB (*color*, *style*)

color is of LOGICAL type, specifies the OFF/ON color of a line and is an integer expression of either 0 (OFF, black) or 1 (ON, white).

style is of INTEGER type, and specifies the pattern of the line. -1 indicates a solid line.

LINEB is the same as LINE except LINEB draws a box between the two sets of coordinates set by the SETXY or SETXYR subroutines.

Example

```
CALL LINEB(1,-1)
```

Line Program (see LINE)

LINEBF

Draws Painted Box

LINEBF (*color*)

color is of LOGICAL type, specifies the OFF/ON color of a line and is an integer expression of either 0 (OFF, black) or 1 (ON, white).

LINEBF is the same as LINEB except LINEBF fills the box (colors in the box) and the argument style is not used.

Example

```
CALL LINEBF (1)
```

Sample Program (see LINE)

LOCATE

Sets the Direction for Displaying Text on the Graphics Screen

LOCATE (*direction*)

direction is of LOGICAL type, specifies the direction that GLOCATE will use to display textual data and is an integer expression of 0-3.

LOCATE sets the direction that GPRINT will use to display textual data. The allowable values for *direction* are:

- 0 - zero degree angle
- 1 - 90 degree angle
- 2 - 180 degree angle
- 3 - 270 degree angle

Examples

```
CALL LOCATE (0)
```

This program line will cause characters to be displayed at the current (x,y) coordinates in normal left to right orientation.

```
CALL LOCATE (1)
```

This program line will cause characters to be displayed at the current (x,y) coordinates in a vertical orientation going from the top of the screen to the bottom of the screen.

```
CALL LOCATE (2)
```

This program line will cause characters to be displayed upside down starting at the right of the screen and going towards the left.

Model 4 Computer Graphics

CALL LOCATE (3)

This program line will cause the characters to be displayed vertically starting at the lower portion of the screen going towards the top of the screen.

PAINT

Paints Screen in Specified Color

PAINT (color, border)

color is of LOGICAL type, specifies the OFF/ON color of painting and is an integer expression of either 0 (OFF, black) or 1 (ON, white).

border is of LOGICAL type, specifies the OFF/ON color of the border and is an integer expression of either 0 (OFF, black) or 1 (ON, white).

PAINT paints the screen in the specified OFF/ON *color* (black or white). It uses the current X- and Y- coordinates (see SETXY) as its startpoint.

Example

CALL PAINT(1,1)

Sample Program (see CIRCLE)

PAINTT

Paints Screen in Specified Pattern

PAINTT (arrayT, border, arrayS)

arrayT is a byte array which defines a multi-pixel pattern to be used when painting (tiling). The first byte of *arrayT* indicates the length of the "tile" (number of bytes).

border is of LOGICAL type and specifies the color of the border. *border* is an integer expression of either 0 (black) or 1 (white).

arrayS is a byte array that is used to define the background. The first byte is always set to 1; the second byte describes the background you are painting on (X'FF' = white, X'00' = black).

PAINTT lets you paint a precisely defined pattern using a graphics technique called "tiling." You can paint with tiling by defining a multi-pixel grid in an array and then using that array as the paint pattern.

Example

CALL PAINTT (A,1,V)

Graphics Subroutine Library (FORTRAN)

Sample Program

```
00100  C   EXAMPLE FOR PAINT WITH TILE
00150      LOGICAL A,B,BORDER
00200      DIMENSION A(9)
00300      DIMENSION B(2)
00350  C   DEFINE TILE ARRAY HERE
00400      DATA A(1), A(2), A(3) / 8, X'81', X'42' /
00500      DATA A(4), A(5), A(6) / X'24', X'18', X'18' /
00600      DATA A(7), A(8), A(9) / X'24', X'42', X'81' /
00650  C   DEFINE BACKGROUND ARRAY HERE
00700      DATA B(1), B(2) / 1, 0 /
00800      CALL GRPINI(0)
00900      CALL CLS
01000      CALL SETXY(300, 100)
01100      CALL CIRCLE(150, 1, 0.0, 0.0, 0.0)
01200      BORDER=1
01300      CALL PAINTT(A, BORDER, B)
01400      END
```

PRESET

Sets Pixel ON/OFF

PRESET (*color*)

color is of LOGICAL type, specifies whether a pixel is to be set ON or OFF and is an integer expression of either 0 (OFF) or 1 (ON).

PRESET sets the pixel defined by the current (x,y) coordinates either ON or OFF.

Example

```
CALL PRESET(0)
```

Sample Program

```
00100  C   PRESET EXAMPLE
00200      LOGICAL COLOR
00300      COLOR=1
00400      CALL GRPINI(0)
00500      CALL CLS
00600  C   SET PIXEL TO ON
00700      CALL SETXY(300, 120)
00800      CALL PRESET(COLOR)
00900  C   TEST PIXEL WHETHER ON OR OFF
01000      K=POINT(M)
01100  30    WRITE (3,35) K
01200  35    FORMAT ('2', 'PIXEL VALUE IS', I4)
01300      END
```

PSET

Sets Pixel ON/OFF

PSET (color)

color is of LOGICAL type, specifies whether a pixel is to be set ON or OFF and is an integer expression of either 0 (OFF) or 1 (ON).

PSET sets the pixel defined by the current (x,y) coordinates either ON or OFF.

Example

```
CALL PSET(0)
```

Sample Program

```
00100  C    PSET EXAMPLE
00200      LOGICAL COLOR
00300      LOGICAL POINT
00400      COLOR=1
00500      CALL GRPINI(0)
00600      CALL CLS
00700  C    SET PIXEL TO ON
00800      CALL SETXY(300,120)
00900      CALL PSET(COLOR)
01000  C    TEST PIXEL WHETHER ON OR OFF
01100      K=POINT(M)
01200      WRITE (3,35)K
01300  35   FORMAT ('2','PIXEL VALUE IS',I4)
01400      END
```

PUT

Puts Stored Array onto Screen

PUT (array, action)

array is usually LOGICAL type, although any type is permissible. Specifies the array (stored with GET) to be restored.

action is of LOGICAL type and specifies how the data is to be written to the video. Action may be one of the following:

1 = OR	3 = PRESET
2 = AND	4 = PSET
	5 = XOR

PUT takes a rectangular pixel area that has been stored by GET and puts it on the screen at current x and y coordinates set by calling SETXY.

Graphics Subroutine Library (FORTRAN)

Example

```
CALL PUT (V,1)
```

Sample Program (see GET)

SCREEN Selects Screen

SCREEN (*switch*)

switch is of LOGICAL type and specifies the type of screen display and may be one of the following:

0 = Graphics Screen
1 = Text Screen

SCREEN lets you select the proper screen.

Example

```
CALL SCREEN(0)
```

Sample Program

This example turns off the graphics display, draws a circle, then turns on the graphics display. The circle is then visible.

```
00010  C      EXAMPLE FOR SCREEN
00020          LOGICAL CMD
00040          CMD=1
00050          CALL GRPINI(0)
00060          CALL CLS
00070          CALL SCREEN(CMD)
00080          CALL SETXY(300,120)
00090          CALL CIRCLE(100,1,0.0,0.0,0.0)
00100          CALL PAINT(1,1)
00110          DO 20 I=1,10000
00120  20      CONTINUE
00130          CMD=0
00140          CALL SCREEN(CMD)
00150          END
```

SETXY Sets Coordinates

SETXY (x,y)

(x,y) are INTEGER type and represent coordinates on the Graphics Screen.

SETXY sets and holds both current and previous X- and Y- coordinates. When a new coordinate is given, it is designated as the "current coordinate" and the last coordinate is designated as the "previous coordinate." If a new coordinate is specified, the "previous coordinate" is lost and the "current coordinate" becomes the "previous coordinate."

Example

```
CALL SETXY(100,100)
```

Sample Program (see LINE)

SETXYR Sets Relative Coordinates

SETXYR (p1,p2)

(p1,p2) are INTEGER type and represent Relative Coordinates on the Graphics Screen.

SETXYR sets the current (x,y) coordinates relative to the previously set (x,y) coordinates. For example, if the "current" coordinates are (100,100), CALL SETXYR(10,10) will set the "current" coordinates to (110,110); the "previous" coordinates will then be (100,100).

Example

```
CALL SETXYR(30,30)
```

Sample Program

```
00010  C    DRAW TWO INTERSECTING CIRCLES
00020      CALL GRPINI(1)
00030      CALL CLS
00040      CALL SETXY(100,100)
00050      CALL CIRCLE(50,1,0.0,0.0,0.0)
00060  C    DRAW SECOND CIRCLE WITH CENTER 20
00070  C    PIXELS TO THE RIGHT OF FIRST CIRCLE
00080      CALL SETXYR(20,0)
00090      CALL CIRCLE(50,1,0.0,0.0,0.0)
00100      END
```

VIEW

Sets Viewport

VIEW (leftX,leftY,rightX,rightY,color,border)

leftX, leftY, rightX, rightY are INTEGER type and specify the viewport's parameters.

left X and rightX are numeric expressions from 0 to 639 and specify viewport's corner

X-coordinates. **leftY** and **rightY** are numeric expressions from 0 to 239 and specify the viewport's corner Y-coordinates.

color is of LOGICAL type, specifies the OFF/ON color code and is a numeric expression of either 0 (OFF, black), 1 (ON, white), or -1 (viewport is not shaded).

border is of LOGICAL type, specifies the border color for the viewport and is an integer expression of either 0 (OFF, black), 1 (ON, white), or -1 (border is not drawn).

VIEW draws viewports on your screen. Graphics is displayed only in the last defined viewport.

The upper-left corner of viewport is read as (0,0) (the "relative origin") when creating items inside the viewport. All the other coordinates are read relative to this origin. However, the "absolute coordinates" of the viewport, as they are actually defined on the Graphics Cartesian system, are retained in memory and can be read using VIEW as a function.

Example

```
CALL VIEW(100,100,200,200,0,1)
```

Sample Program

```
00100  C    SAMPLE VIEW PROGRAM
00200      LOGICAL COLOR,BORDER,K
00300      INTEGER FVIEW
00400      CALL GRPINI(1)
00500      CALL CLS
00600  C    SET UP VIEW PORT
00700      COLOR=0
00800      BORDER=1
00900      CALL VIEW(210,80,420,160,COLOR,BORDER)
01000  C    DRAW MULTIPLE CIRCLES
01100      CALL SETXY(105,40)
01200      DO 20 I=10,150,10
01300      CALL CIRCLE(I,1,0.0,0.0,0)
01400  20    CONTINUE
01500  C    DISPLAY VIEWPORT COORDINATES
01600      DO 40 I=1,4
01700      K=I-1
01800      J=FVIEW(K)
01900      WRITE (3,35) I,J
02000  35    FORMAT ('2','VIEW PORT COORDINATE ',I4,' IS AT ',I4)
02100  40    CONTINUE
02200  C    PRINT EMPTY LINES
```

```
02300      DO 60 I=1,6
02400      WRITE (3,50)
02500 50    FORMAT (1H1)
02600 60    CONTINUE
02700      END
```

The following two descriptions are functions in the Graphics Subroutine Library and must be declared as LOGICAL and INTEGER, respectively, in any routine that uses them.

Functions

POINT

Reads Pixel Value at Current Coordinates

V = POINT(X)

X is a dummy variable needed to set up the proper FORTRAN linkage to the POINT routine.

POINT returns the OFF/ON pixel value at current x and y coordinate as specified by SETXY or SETXYR. If the point is not in the current viewport, POINT returns -1.

Example

```
K = POINT(M)
```

Sample Program (see PSET)

FVIEW

Reads Viewport's Parameters

FVIEW (n)

n is of LOGICAL type and is an integer expression from 0 to 3.

FVIEW returns the specified viewport parameter:

- 0 = returns the left X-coordinate
- 1 = returns the left Y-coordinate
- 2 = returns the right X-coordinate
- 3 = returns the right Y-coordinate

Example

```
I = FVIEW(0)
```

Sample Program (see VIEW)

5/ Programming the Graphics Board

The Graphics Board provides 640×240 byte addressable pixels on a TRS-80 Model 4. The Graphics Board contains 32K of screen RAM to store video data consisting of four 64K RAMs which are double accessed for 8 bytes of data. Regular alphanumeric data is stored in the static RAM on the Video Board. The Graphics Board uses separate hardware to generate a 640×240 display, so only one screen may be displayed at a time. If the video is switched from Text to Graphics Screen very rapidly, the Video display may lose horizontal/vertical synchronization.

I/O port mapping is used to read and write data to the board. The Board is addressable at 80 – 83 Hex.

There are four internal registers which can be written to or read on the board. They are as follows:

1. X-Position — X-address (0 to 127) for data write only. (0 to 79 for display.)
2. Y-Position — Y-address (0 to 255) for data write only. (0 to 238 for display.)
3. Data — Graphics data in “byte” form. Each byte turns on or off 8 consecutive horizontal dots.
4. Options — 8 flags which turn on or off the user programmable options (Write only).

The I/O port mapping of the board is:

- x0 — X-Register Write. (80)
- x1 — Y-Register Write. (81)
- x2 — Video data read or write. (82)
- x3 — Options write. (83)

where x denotes the upper nibble of the I/O boundary as set by the DIP Switches. They are set by the factory at 80H.

The Graphics Board uses X-Y addressing to locate the start of a Graphics data byte. The upper-left of the screen is (0,0) while the lower-right is (079,239). If the bit is a 1, the dot will be ON. For example, if you wanted to turn on the 5th dot on the top row, the registers would contain: X POSITION = 0, Y POSITION = 0, DATA = (00001000) = 08H. Note that in calculating points to plot, the Y-position is correct for a single dot. Only the X-position must be corrected to compensate for the byte addressing. This can be accomplished in a simple subroutine.

Line Drawing Options

There are two 8-bit counters which act as latches for the X- and Y-address. You may select, through the options register, if they are to automatically count after a read or write to graphic memory. Also, the counters may increment or decrement independently. These counters do not count to their respective endpoints and reset. Instead, they will overflow past displayable video addresses. Therefore, the software should not allow the counters to go past 79 and 239. However, these extra memory locations may be used for data storage.

Model 4 Computer Graphics

Examples

The following are brief examples on how to use the Graphics Board.

Read the video byte at X=0, Y=0

```
XOR      A                ;CLEAR A
OUT      (80H),A           ;OUTPUT X ADDRESS
OUT      (81H),A           ;OUTPUT Y ADDRESS
IN       A,(82H)           ;READ VIDEO BYTE
```

Draw a line from X=0,Y=0 to X=639, Y=0 using the hardware line drawing

```
LD       B,79              ;B HAS CHARACTER COUNT
LD       A,0B1H            ;OPTIONS: INCREMENT X AFTER WRITE
                          ;10110001 Binary

OUT      (83H),A
XOR      A
OUT      (80H),A           ;OUT X ADDRESS STARTING
OUT      (81H),A           ;OUTPUT Y ADDRESS
LD       A,0FFH            ;LOAD A WITH ALL DOTS ON
LOOP OUT (82H),A           ;OUTPUT DOTS
DJNZ     LOOP              ;OUTPUT NUMBER IN B REGISTER
```

Options Programming

No.	Option	Description
0	GRAPHICS/ALPHA*	Turns graphics ON and OFF. "1" turns graphics ON.
1	NOT USED	
2	XREG DEC/INC*	Selects whether X decrements or increments. "1" selects decrement.
3	YREG DEC/INC*	Selects whether Y decrements or increments. "1" selects decrement.
4	X CLK RD*	If address clocking is desired, a "0" clocks the X address up or down AFTER a Read depending on the status of BIT 2.
5	Y CLK RD*	If address clocking is desired, a "0" clocks the Y address up or down AFTER a Read depending on the status of BIT 3.
6	X CLK WR*	A "0" clocks AFTER a Write.
7	Y CLK WR*	A "0" clocks AFTER a Write.

Table 9. Options Programming

Appendix A/BASICG/Utilities Reference Summary

Argument ranges are indicated below by special letters and words:

ar is a single-precision floating point number > 0.0 (to $1 * 10^{38}$).

<i>b</i>	is an integer expression of either 0 or 1.
B	specifies a box.
BF	specifies a shaded box.
<i>c</i>	is an integer expression of 0 or 1.
<i>n</i>	is an integer expression from 0 to 2.
<i>p</i>	is an integer expression from 0 to 3.
<i>r</i>	is an integer expression from 0 to 639.
<i>x</i>	is an integer expression from 0 to 639.
<i>y</i>	is an integer expression from 0 to 239.
<i>action</i>	is either AND, PSET, PRESET, OR, or XOR.
<i>background</i>	is a string of either 0 or 1.
<i>border</i>	is an integer expression of either 0 or 1.
<i>end</i>	is an expression from -6.283185 to 6.283185 .
<i>start</i>	<i>f029</i> is an expression from -6.283185 to 6.283185 .
<i>switch</i>	is an integer expression of 0 or 1.
<i>tiling</i>	is a string or an integer expression of 0 or 1.
<i>type</i>	is an integer expression of 0 or 1.

CIRCLE(*x,y*),*r,c,start,end,ar* Draws a circle, ellipse, semicircle, arc, or point.

```
CIRCLE(100,100),25,1          CIRCLE(150,150),40,1,,,6
CIRCLE(100,100),100,PI,2*PI,5  CIRCLE(-50,-50),200
```

CLS Clears the Text Screen and video memory.

```
CLS          SYSTEM"CLS"
```

CLR Clears the Graphics Screen.

```
CLR
```

GCLS Clears the Graphics Screen and memory.

```
GCLS          SYSTEM"GCLS"          100 SYSTEM"GCLS"
```

GET(*x1,y1*)-(*x2,y2*),*array name* Reads the contents of a rectangular pixel area into an array.

```
GET(10,10)-(50,50),V
```

GLOAD *filename/ext.password:d* Loads graphics memory.

```
GLOAD PROG          SYSTEM"GLOAD PROG"
```

GLOCATE (*x,y*),*direction* Sets the Graphics Cursor

```
GLOCATE (320,120),0
```

Model 4 Computer Graphics

GPRINT Dumps graphic display on the printer.

GPRINT SYSTEM"GPRINT" 100 SYSTEM"GPRINT"

GPRT2 Dumps graphic display on the printer without rotating 90 degrees.

GPRT2 SYSTEM"GPRT2" 100 SYSTEM"GPRT2"

GPRT3 Dumps graphics display on the printer without rotating 90 degrees.

GPRT3 SYSTEM"GPRT3" 100 SYSTEM"GPRT3"

GROFF Turns Graphics Display OFF.

GROFF SYSTEM"GROFF"

GRON Turns Graphics Display ON.

GRON SYSTEM"GRON"

GSAVE filename/ext.password:d Saves graphics memory.

GSAVE PROG SYSTEM"GSAVE PROG"

LINE(x1,y1)-(x2,y2),c,B or BF, style Draws a line/box.

LINE -(100,100) LINE(100,100)-(200,200),1,B,45
LINE(0,0)-(100,100),1,BF LINE(-200,-200)-(100,100)

PAINT(x,y),tiling,border,background Paints the screen.

PAINT(320,120),1,1 PAINT(320,120),"DDDDD",1
PAINT(320,120),A\$,1
PAINT(320,120),CHR\$(0)+CHR\$(&HFF),0,CHR\$(&H00)
PAINT(320,120),CHR\$(E)+CHR\$(77)+CHR\$(3)

&POINT(x,y) A function. Tests graphics point.

PRINT &POINT(320,120) IF &POINT(320,120)=1 THEN...
PRINT &POINT(320,120),-1

PRESET(x,y),switch Sets pixel OFF or ON.

PRESET(100,100),0

PRINT #-3, item list Write text characters to the Graphics Screen.

PRINT #-3,"MONTHLY"

PSET(x,y),switch Sets pixel ON or OFF.

PSET(100,100),1

PUT(x1,y1),array name,action Puts graphics from an array onto the screen.

PUT(100,100),A,PSET PUT(100,100),A,AND
PUT(A,B),B

SCREEN type Selects the screen.

SCREEN 0

VIEW(x1,y1)-(x2,y2),c,b Redefines the screen and creates a viewport.

VIEW(100,100)-(150,150) VIEW(100,100)-(150,150),0,1

&VIEW(p) A function. Returns viewport's coordinates.

PRINT &VIEW(1)

Appendix B/ BASIC Error Codes and Messages

Code	Number	Message
NF	1	<p>NEXT without FOR</p> <p>A variable in a NEXT statement does not correspond to any previously executed, unmatched FOR statement variable.</p>
SN	2	<p>Syntax error</p> <p>BASIC encountered a line that contains an incorrect sequence of characters (such as unmatched parenthesis, misspelled statement, incorrect punctuation, etc.). BASIC automatically enters the edit mode at the line that caused the error.</p>
RG	3	<p>Return without GOSUB</p> <p>BASIC encountered a RETURN statement for which there is no matching GOSUB statement.</p>
OD	4	<p>Out of data</p> <p>BASIC encountered a READ statement, but no DATA statements with unread items remain in the program.</p>
FC	5	<p>Illegal function call</p> <p>A parameter that is out of range was passed to a math or string function. An FC error may also occur as the result of:</p> <ol style="list-style-type: none">A negative or unreasonably large subscript.A negative or zero argument with LOG.A negative argument to SQU.A negative mantissa with a noninteger exponent.A call to a USR function for which the starting address has not yet been given.An improper argument to MID\$, LEFT\$, RIGHT\$, PEEK, POKE, TAB, SPC, STRING\$, SPACE\$, INSTR, or ON...GOTO.
OV	6	<p>Overflow</p> <p>The result of a calculation was too large to be represented in BASIC numeric format. If underflow occurs, the result is zero and execution continues without an error.</p>

Model 4 Computer Graphics

OM	7	Out of memory A program is too large, or has too many FOR loops or GOSUBs, too many variables, or expressions that are too complicated.
UL	8	Undefined line number A nonexistent line was referenced in a GOTO, GOSUB, IF...THEN...ELSE, or DELETE statement.
BS	9	Subscript out of range An array element was referenced either with a subscript that is outside the dimensions of the array, or with the wrong number of subscripts.
DD	10	Redimensioned Array Two DIM statements were given for the same array, or a DIM statement was given for an array after the default dimension of 10 has been established for that array.
/O	11	Division by zero An expression includes division by zero, or the operation of involution results in zero being raised to a negative power. BASIC supplies machine infinity with the sign of the numerator as the result of the division, or it supplies positive machine infinity as the result of the involution. Execution then continues.
ID	12	Illegal direct A statement that is illegal in direct mode was entered as a direct mode command.
TM	13	Type mismatch A string variable name was assigned a numeric value or vice versa. A numeric function was given a string argument or vice versa.
OS	14	Out of string space String variables have caused BASIC to exceed the amount of free memory remaining. BASIC allocates string space dynamically, until it runs out of memory.
LS	15	String too long An attempt was made to create a string more than 255 characters long.
ST	16	String formula too complex A string expression is too long or too complex. The expression should be broken into smaller expressions.

Appendix B/ BASICG Error Codes and Messages

CN	17	Can't continue An attempt was made to continue a program that: a. Has halted due to an error. b. Has been modified during a break in execution. c. Does not exist.
UF	18	Undefined user function A USR function was called before providing a function definition (DEF) statement.
	19	No RESUME An error-handling routine was entered without a matching RESUME statement.
	20	RESUME without error A RESUME statement was encountered prior to an error-handling routine.
	21	Undefined error An error message is not available for the error that occurred.
	22	Missing operand An expression contains an operator with no operand.
	23	Line buffer overflow. An attempt was made to input a line with too many characters.
	26	FOR without NEXT A FOR statement was encountered without a matching NEXT.
	29	WHILE without WEND A WHILE statement does not have a matching WEND.
	30	WEND without WHILE A WEND statement was encountered without a matching WHILE.
Disk Errors		
	50	Field overflow A FIELD statement is attempting to allocate more bytes than were specified for the record length of a direct-access file.

Model 4 Computer Graphics

- 51 Internal error**
An internal error malfunction has occurred in BASIC. Report to Radio Shack the conditions under which the message appeared.
- 52 Bad file number**
A statement or command references a file with a buffer number that is not OPEN or is out of the range of file numbers specified at initialization.
- 53 File not found**
A LOAD, KILL, or OPEN statement references a file that does not exist on the current disk.
- 54 Bad file mode**
An attempt was made to use PUT, GET, or LOF with a sequential file, to LOAD a direct file, or to execute an OPEN statement with a file mode other than I, O, R, E or D.
- 55 File already open**
An OPEN statement for sequential output was issued for a file that is already open; or a KILL statement was given for a file that is open.
- 57 Device I/O error**
An Input/Output error occurred. This is a fatal error; the operating system cannot recover it.
- 58 File already exists**
The filespec specified in a NAME statement is identical to a filespec already in use on the disk.
- 61 Disk full**
All disk storage space is in use.
- 62 Input past end**
An INPUT statement was executed after all the data in the file had been INPUT, or for a null (empty) file. To avoid this error, use the EOF function to detect the end-of-file.
- 63 Bad record number**
In a PUT or GET statement, the record number is either greater than the maximum allowed (65,535) or equal to zero.

Appendix B/ BASICG Error Codes and Messages

- | | |
|----|---|
| 64 | Bad file name
An illegal filespec (file name) was used with a LOAD, SAVE, KILL, or OPEN statement (for example, a filespec with too many characters). |
| 66 | Direct statement in file
A direct statement was encountered while LOADING an ASCII-format file. The LOAD is terminated. |
| 67 | Too many files
An attempt was made to create a new file (using SAVE or OPEN) when all directory entries are full. |

Appendix C/ Subroutine Language Reference Summary

CIRCLE (*radius, color, start, end, ar*) Draws circle, ellipse, semicircle, arc, or point. (x,y) coordinates set by SETXY.

```
CALL CIRCLE (100,1,0,0,0)
```

CLS Clears Screen.

```
CALL CLS(2)
```

FVIEW (*n*) Returns viewport parameter.

```
I=FVIEW(0)
```

GET (*array, size*) Reads the contents of a rectangular pixel area into an array for future use by PUT.

```
CALL GET(A,4000)
```

GPRINT (*size, array*) Displays textual data.

```
CALL GPRINT (28,ARRAY1)
```

GRPINI (*option*) Graphics initialization routine.

```
CALL GRPINI(0)
```

LINE (*color, style*) Draws a line.

Coordinates set by SETXY or SETXYR.

```
CALL LINE (1,-1)
```

LINEB (*color, style*) Draws a box.

Coordinates set by SETXY or SETXYR.

```
CALL LINEB (1,-1)
```

LINEBF (*color*) Draws a filled box.

Coordinates set by SETXY or SETXYR.

```
CALL LINEBF (1)
```

LOCATE (*n*) Sets the direction for displaying textual data.

```
CALL LOCATE
```

PAINT (*color, border*) Paints screen.

```
CALL PAINT(1,1)
```

PAINTT (*arrayT, border, arrayS*) Paints screen with defined paint style.

```
CALL PAINTT (A,1,V)
```

POINT Returns pixel value at current coordinates.

```
K=POINT(M)
```

PRESET (*color*) Sets pixel ON or OFF.

```
CALL PRESET (0)
```

PSET (*color*) Sets pixel ON or OFF.

```
CALL PSET (0)
```

Model 4 Computer Graphics

SCREEN (*type*) Sets Screen/graphics speed.

CALL SCREEN (1)

SETXY (*X,Y*) Sets coordinates (absolute).

CALL SETXY(100,100)

SETXYR(*X,Y*) Sets coordinates (relative).

CALL SETXYR(50,50)

VIEW (*leftX,leftY,rightX,rightY,color,border*) Sets viewport.

CALL VIEW(100,100,200,200,0,1)

Appendix D/ Sample Programs

```
10 /
20 / Pie Graph Program ("PECANPIE/GRA")
30 /
40 / Object
50 /     The object of this program is to draw a pie graph of the
60 /     expenses for a given month of eight departments of a company,
70 /     along with the numerical value of each pie section
80 /     representation.
90 /
100 /
110 / Running the program
120 /     The month and the amounts spent by each department are input,
130 /     and the program takes over from there.
140 /
150 / Special features
160 /     The amounts spent by each account as well as the total
170 /     amount spent are stored in strings. The program will
180 /     standardize each string so that it is 9 characters long
190 /     and includes two characters to the right of the decimal
200 /     point. This allows for input of variable length and an
210 /     optional decimal point.
220 /
230 /     The various coordinates used in the program are found
240 /     based on the following equations:
250 /
260 /         x = r * cos(theta)
270 /         y = r * sin(theta)
280 /
290 /     where x and y are the coordinates, r is the radius, and theta
300 /     is the angle. (Note: The y-coordinates are always multiplied
310 /     by 0.5. This is because the y pixels are twice the size of the
320 /     x pixels.)
330 /
340 /     If an angle theta is generated by a percent less than 1%, the
350 /     section is not graphed, and the next theta is calculated.
360 /     However, the number will still be listed under the key.
370 /
380 / Variables
390 /     ACCT$(i)      Description of the account
400 /     BUD$(i)       Amount spent by the account
410 /     DS$           Dollar sign (used in output)
420 /     HXCOL         Column number for the pie section number
430 /     HYRW          Row number for the pie section number
440 /     I             Counter
```

Model 4 Computer Graphics

```
450 ' MN$ Month
460 ' PER(i) Percent value of BUD$(i)
470 ' R Radius of circle
480 ' T0 Angle value line to be drawn
490 ' T1 Angle value of the next line
500 ' TBUD$ Total of all the BUD$(i)'s
510 ' THALF Angle halfway between T1 and T0 (used for
520 ' location position for section number)
530 ' TILE$(i) Paint style for each section
540 ' TWOPI Two times the value of pi
550 ' X0 X-coordinate for drawing the line represented
560 ' by T0
570 ' XP X-coordinate for painting a section
580 ' Y0 Y-coordinate for drawing the line represented
590 ' by T0
600 ' YP Y-coordinate for painting a section
610 '
620 ' Set initial values
630 '
640 CLEAR 1000 '10-JAN-84
650 DIM THALF(15),BUD$(15),ACCT$(15),PER(16)
660 TWOPI=2*3.14159
670 R=180
680 DS$="$"
690 ACCT$(1) = "Sales"
700 ACCT$(2) = "Purchasing"
710 ACCT$(3) = "R&D"
720 ACCT$(4) = "Accounting"
740 ACCT$(5) = "Advertising"
750 ACCT$(6) = "Utilities"
760 ACCT$(7) = "Security"
770 ACCT$(8) = "Expansion"
780 TILE$(0)=CHR$(&H22)+CHR$(&H0)
790 TILE$(1)=CHR$(&HFF)+CHR$(&H0)
800 TILE$(2)=CHR$(&H99)+CHR$(&H66)
810 TILE$(3)=CHR$(&H99)
820 TILE$(4)=CHR$(&HFF)
830 TILE$(5)=CHR$(&HF0)+CHR$(&HF0)+CHR$(&HF)+CHR$(&HF)
840 TILE$(6)=CHR$(&H3C)+CHR$(&H3C)+CHR$(&HFF)
850 TILE$(7)=CHR$(&H3)+CHR$(&HC)+CHR$(&H30)+CHR$(&HC0)
860 '
870 ' Enter values to be graphed, standardize them, and calculate
880 ' the percent they represent
890 '
900 CLR
910 CLS
920 SCREEN 1
930 PRINT @80,"Enter month "
940 PRINT @240,"Enter amount spent by"
```

Appendix D/ Sample Programs

```
950 PRINT @320,"$"
960 PRINT @0,""
970 LINE INPUT "Enter month ";MN$
980 FOR I=1 TO 8
990 PRINT @265,ACCT$(I);"
1000 PRINT @320,"$"
1010 PRINT @240,""
1020 LINE INPUT "$";BUD$(I)
1030 IF INSTR(BUD$(I),",")=0 THEN BUD$(I)=BUD$(I)+",.00"
1040 IF LEN(BUD$(I))<9 THEN BUD$(I)=" "+BUD$(I):GOTO 1040
1050 TBUD$=STR$(VAL(TBUD$)+VAL(BUD$(I)))
1060 NEXT I
1070 IF INSTR(TBUD$,",")=0 THEN TBUD$=TBUD$+",.00"
1080 IF LEN(TBUD$)<9 THEN TBUD$=" "+TBUD$:GOTO 1080
1090 FOR I=1 TO 8
1100 PER(I)=VAL(BUD$(I))/VAL(TBUD$)*100
1110 NEXT I
1120 SCREEN 0
1130 '
1140 ' Draw the circle and calculate the location of the lines and
1150 ' the line numbers
1160 '
1170 CIRCLE(425,120),R
1180 FOR I=0 TO 8
1190 T0=TWOPI/100*PER(I)=T0
1200 X0=425+R*COS(T0)
1210 Y0=120-R*SIN(T0)*.5
1220 T1=TWOPI/100*PER(I+1)+T0
1230 THALF(I)=(T0+T1)/2
1240 HXCOL=(425+R*1.15*COS(THALF(I)))-10
1250 HYRW=INT(120-R*1.15*SIN(THALF(I))*5)
1260 IF PER(I)>1 THEN LINE (425,120)-(X0,Y0)
1270 GLOCATE (HXCOL,HYRW),0
1280 IF I<8 and PER(I+1)>1 THEN PRINT #,-3,I+1
1290 NEXT I
1300 '
1310 ' Paint the appropriate sections of the pie
1320 '
1330 FOR I=0 TO 7
1340 XP=425+R*.5*COS(THALF(I))
1350 YP=120-R*.5*SIN(THALF(I))*5
1360 IF PER(I+1)<=1 THEN 1380
1370 PAINT (XP,YP),TILE$(I),1
1380 NEXT I
1390 '
1400 ' Print the key for the graph
1410 '
1420 GLOCATE(0,10),0
```

Model 4 Computer Graphics

```
1430 PRINT #-3,"Expenditures for"
1440 GLOCATE(0,25),0
1450 PRINT #-3,MN$
1460 GLOCATE(0,40),0
1470 PRINT #-3,"#      Description      Amount"
1480 FOR I=1 TO 8
1490 GLOCATE(0,(4+I)*15),0
1500 PRINT #-3,I
1510 GLOCATE(40,(4+I)*15),0
1520 PRINT #-3,ACCT$(I)
1530 GLOCATE(130,(I+4)*15),0
1540 PRINT #-3,DS$;BUD$(I)
1550 DS$=" "
1560 NEXT I
1570 GLOCATE(0,195),0
1580 PRINT #-3,STRING$(26,"-")
1590 GLOCATE(40,210),0
1600 PRINT #-3,"Total          ";TBUD$
1610 FOR I=1 TO 10000
1620 NEXT I
1630 SCREEN 1
1640 END
```

Appendix D/ Sample Programs

```
10 / "THREEDDEE/GRA"
20 /
30 / Object
40 /   The object of this program is to produce a three
50 / dimensional bar graph representation of the gross
60 / income for a company over a one year period.
70 /
80 / Variables
90 /   A      Vertical alphanumeric character
100 /   BMSG$   Bottom message
110 /   CHAR$   Disk file input field
120 /   GI$     Gross income
130 /   I       Counter
140 /   J       Counter
150 /   MN$     Month
160 /   REC     Record number of vertical character
170 /   S1$     Single character of vertical message
180 /   TILE$   Tile pattern for painting
190 /   TTINC   Total income for the year
200 /   X       X-coordinate of bar
210 /   Y(i)    Y-coordinate of bar
220 /
230 / Input/output
240 /   The program prompts you to enter the gross income, in millions,
250 / for each month. The program requires these values to be between one
260 / and nine.
270 /
280 / Set initial values
290 /
300 CLS
310 DIM Y(12),A(8),MN$(12)
320 DEFINT A
330 VMSG$=" Millions of dollars "
340 TMSG$="G r o s s   I n c o m e   F o r   1 9 8 3 "
350 BMSG$="M o n t h"
360 MN$(1)="January"
370 MN$(2)="February"
380 MN$(3)="March"
390 MN$(4)="April"
400 MN$(5)="May"
410 MN$(6)="June"
420 MN$(7)="July"
430 MN$(8)="August"
440 MN$(9)="September"
450 MN$(10)="October"
460 MN$(11)="November"
470 MN$(12)="December"
480 TILE$=CHR$(&H99)+CHR$(&H66)
```

Model 4 Computer Graphics

```
490 X=-10
500 '
510 ' Input gross income, and calculate the Y-coordinate
520 '
530 FOR I=1 TO 12
540 CLS
550 PRINT "Enter gross income in millions (1-9) for ";MN$(I)
560 LINE INPUT "$";GI$
570 Y(I)=205-20*VAL(GI$)
580 TTINC=TTINC+VAL(GI$)
590 NEXT I
600 CLR
610 SCREEN 0
620 '
630 ' Draw the graph and bars
640 '
650 FOR I=1 TO 12
660 CLS
670 X=X+50
680 LINE (X,Y(I))-(X+20,205),1,BF
690 LINE -(X+40,195)
700 LINE -(X+40,Y(I)-10)
710 LINE -(X+20,Y(I)-10)
720 LINE -(X,Y(I))
730 LINE (X+20,Y(I))-(X+40,Y(I)-10)
740 PAINT(X+21,Y(I)+2),TILE$,1
750 NEXT I
760 GLOCATE(40,215),0
770 PRINT #3,"Jan Feb Mar Apr May June July Aug Sept Oct Nov Dec"
780 GLOCATE(290,230),0
790 PRINT #3,BMSG$
800 FOR I=1 TO 10
810 IF I>9 THEN C=1 ELSE C=2
820 GLOCATE((C*10)-5,(20-I*2)*10),0
830 PRINT #3,STR$(I);"- "
840 NEXT I
850 LINE (35,0)-(35,205)
860 LINE -(639,205)
870 GLOCATE(0,180),3
880 PRINT #3,VMSG$
890 GLOCATE(220,0),0
900 PRINT #3,TMSG$
910 GLOCATE(260,10),0
920 PRINT #3,"(Total income is";TTINC;" million)"
930 FOR I=1 TO 10000
940 NEXT I
950 SCREEN 1
960 END
```


Printing Graphics Displays

There are many ways to use the stand-alone utilities (described in Graphic Utilities). The following discussion demonstrates one way to use the utilities with graphic displays generated under BASICG.

To print graphics, follow these steps:

1. When TRSDOS Ready appears, set FORMS to allow 255 characters per line and 60 lines per page. (See your *Model 4 Disk System Owner's Manual*.)
2. Set the printer into Graphic Mode, if possible, and set the printer's other parameters (elongation, non-elongated, etc.), if applicable, according to instructions in your printer owner's manual.
3. Write, run and save your program as a BASICG program file.
4. Save the graphics memory to diskette using GSAVE.
5. Load the file into memory using GLOAD.
6. Enter the print command GPRINT.

Example

1. Set FORMS with your printer's printing parameters.
2. Load BASICG and type in this program:

```
5 SCREEN 0
10 DEFDBL Y
20 CLR
30 LINE (0,120)-(640,120)
40 LINE (320,0)-(320,240)
50 FOR X=0 TO 640
60 PI=3.141259
70 X1=X/640*2*PI-PI
80 Y=SIN(X1)*100
90 IF Y>100 THEN X=X+7
100 PSET (X,-Y+120)
110 NEXT X
120 GLOCATE(0,0),0
130 PRINT #3, "THIS IS A SINE WAVE."
```

3. RUN the program.

The program draws a sine wave on the Graphics Screen (graphics memory) and prints the statement in line 130 ("THIS IS A SINE WAVE.") on the Graphics Screen.

4. SINE (for sine wave) is the name we are giving this TRSDOS file. To save the contents of the graphics memory (which now includes the converted video memory) to diskette, type: `SYSTEM"GSAVE SINE"` **(ENTER)**.
5. The graphics memory is saved as a TRSDOS file on your diskette.
6. Exit BASIC by typing: `SYSTEM` **(ENTER)**

Model 4 Computer Graphics

7. Type: GCLS (ENTER)

The graphics memory is now cleared.

8. To load the file back into memory, type:

GLOAD SINE (ENTER)

The display is now on the Graphics Screen.

9. To print, type: GPRINT (ENTER).

FORTRAN Sample Programs

```
00100 C      HIGH RESOLUTION GRAPHICS TEST - MAIN PROGRAM
00200 C
00300      CALL GRPINI(0)
00400      CALL SCREEN(0)
00500 C
00600 C      CIRCLE TEST
00700 C
00800      CALL CTEST
00900 C
01000 C      LINE TEST
01100 C
01200      CALL LTEST
01300 C
01400 C      LINEB TEST
01500 C
01600      CALL LBTST
01700 C
01800 C      LINEBF TEST
01900 C
02000      CALL LBFTST
02100 C
02200 C      PAINTT TEST
02300 C
02400      CALL PTTTST
02500 C
02600 C      GET AND PUT TEST
02700 C
02800      CALL GPTST
02900 C
03000 C      PSET/POINT TEST
03100 C
03200      CALL PPTST
03300 C
03400 C      PRESET/POINT TEST
03500 C
03600      CALL PRETST
03700 C
```

Appendix D/ Sample Programs

```
03800 C SCREEN TEST
03900 C
04000 CALL SCRTST
04100 C
04200 C VIEW/FVIEW TEST
04300 C
04400 CALL VTEST
04500 CALL CLS(2)
04600 END
```

Model 4 Computer Graphics

```
00100      SUBROUTINE CTEST
00200      C
00300      C      THIS SUBROUTINE TESTS CIRCLE, SETXY, AND PAINT
00400      C
00500      LOGICAL MSG(29)
00600      CALL CLS
00700      ENCODE(MSG,100)
00800      100  FORMAT('TEST CIRCLE, SETXY, AND PAINT')
00900      CALL SETXY(0,0)
01000      CALL LOCATE(0)
01100      CALL GPRINT(29,MSG)
01200      CALL WAIT
01300      CALL VIEW(0,30,639,239,0,0)
01400      DO 10 I=1,100
01500      IX=MOD(I*17,640)
01600      IY=MOD(I*13,210)
01700      IR=I*1.5
01800      START=MOD(I,13)-6.0
01900      END=MOD(I*3,13)-6.0
02000      IF (START.LT.END) GOTO 1
02100      T=START
02200      START=END
02300      END=T
02400      1  CONTINUE
02500      RATIO=MOD(I*3,100)
02600      IF (RATIO.GT.0) RATIO=RATIO/40.
02700      CALL SETXY(IX,IY)
02800      CALL CIRCLE(IR,1,START,END,RATIO)
02900      10  CONTINUE
03000      C
03100      C      RANDOMLY FILL IN THE AREAS
03200      C
03300      DO 11 I=1,50
03400      IX=MOD(I*23,640)
03500      IY=MOD(I*11,210)
03600      CALL SETXY(IX,IY)
03700      CALL PAINT(1,1)
03800      11  CONTINUE
03900      CALL WAIT
04000      CALL VIEW(0,0,639,239,-1,-1)
04100      RETURN
04200      END
```

Appendix D/ Sample Programs

```

001000      SUBROUTINE LTEST
002000      C
003000      C      THIS ROUTINE EXERCISES LINE
004000      C
005000      LOGICAL MSG(19)
006000      CALL CLS(0)
007000      ENCODE(MSG,100)
008000      100    FORMAT('LINE AND PAINT TEST')
009000      CALL SETXY(0,0)
010000      CALL LOCATE(0)
011000      CALL GPRINT(19,MSG)
012000      CALL WAIT
013000      J=100
014000      DO 10 I=1,639,2
015000      CALL SETXY(I,15)
016000      CALL SETXY(I,239)
017000      CALL LINE(1,J)
018000      J=J-1
019000      10    CONTINUE
020000      CALL WAIT
021000      CALL VIEW(0,15,639,239,0,0)
022000      CALL CLS
023000      C
024000      C      DRAW WHITE LINES AND FILL IN RANDOMLY
025000      C
026000      IX=MOD(I*19,639)
027000      IY=MOD(I*17,223)
028000      CALL SETXY(IX,IY)
029000      DO 11 I=1,100
030000      IX=MOD(I*23,639)
031000      IY=MOD(I*29,223)
032000      CALL SETXY(IX,IY)
033000      CALL LINE(1,-1)
034000      11    CONTINUE
035000      DO 12 I=1,50
036000      IX=MOD(I*31,639)
037000      IY=MOD(I*37,223)
038000      CALL SETXY(IX,IY)
039000      CALL PAINT(1,1)
040000      12    CONTINUE
041000      CALL WAIT
042000      C
043000      C      WHITE OUT SCREEN, DRAW BLACK LINES, PAINT BLACK RANDOMLY
044000      C
045000      CALL VIEW(0,15,639,239,1,1)
046000      DO 15 I=1,100
047000      IX=MOD(I*11,639)
048000      IY=MOD(I*13,223)
049000      CALL SETXY(IX,IY)
050000      CALL LINE(0,-1)
051000      15    CONTINUE
052000      DO 16 I=1,50
053000      IX=MOD(I*17,639)

```

Model 4 Computer Graphics

```
05400      IY=MOD(I*19,223)
05500      CALL SETXY(IX,IY)
05600      CALL PAINT(0,0)
05700  16    CONTINUE
05800      CALL WAIT
05900      CALL VIEW(0,0,639,239,0,0)
06000      RETURN
06100      END
```

Appendix D/ Sample Programs

```
00100 SUBROUTINE LBFTST
00200 C
00300 C LINEBF TEST
00400 C
00500 LOGICAL MSG(11)
00600 CALL CLS
00700 ENCODE(MSG,100)
00800 100 FORMAT('LINEBF TEST')
00900 CALL SETXY(0,0)
01000 CALL LOCATE(0)
01100 CALL GPRINT(11,MSG)
01200 CALL WAIT
01300 IXP=639
01400 ICLR=1
01500 DO 10 IX=0,120
01600 CALL SETXY(IX*2,IX+30)
01700 CALL SETXY(IXP,IXP-400)
01800 CALL LINEBF(ICLR)
01900 IXP=IXP-3
02000 ICLR=ICLR-1
02100 IF (ICLR.LT.0) ICLR=1
02200 10 CONTINUE
02300 CALL WAIT
02400 RETURN
02500 END
```

Model 4 Computer Graphics

```

001000      SUBROUTINE PTTTST
002000      C
003000      C      PAINT WITH TILES TEST
004000      C
005000      LOGICAL A(65),B(4),IS(16),MSG(23)
006000      DATA A(1)/8/
007000      C      X
008000      DATA A(2),A(3),A(4),A(5)/X'41',X'22',X'14',X'08'/
009000      DATA A(6),A(7),A(8),A(9)/X'14',X'22',X'41',X'08'/
010000      C      FINE HORIZONTAL LINES
011000      DATA A(10),A(11),A(12)/2,X'FF',X'08'/
012000      C      MEDIUM HORIZONTAL LINES
013000      DATA A(13)/4/
014000      DATA A(14),A(15),A(16),A(17)/X'FF',X'FF',X'08',X'08'/
015000      C      DIAGONAL LINES
016000      DATA A(18)/4/
017000      DATA A(19),A(20),A(21),A(22)/X'03',X'0C',X'30',X'C0'/
018000      C      LEFT TO RIGHT DIAGONALS
019000      DATA A(23)/4/
020000      DATA A(24),A(25),A(26),A(27)/X'C0',X'30',X'0C',X'03'/
021000      C      FINE VERTICAL LINES
022000      DATA A(28),A(29)/1,X'AA'/
023000      C      MEDIUM VERTICAL LINES
024000      DATA A(30),A(31)/1,X'CC'/
025000      C      COARSE VERTICAL LINES
026000      DATA A(32),A(33)/1,X'F0'/
027000      C      ONE PIXEL DOTS
028000      DATA A(34),A(35),A(36)/2,X'22',X'08'/
029000      C      TWO PIXEL DOTS
030000      DATA A(37),A(38),A(39)/2,X'99',X'66'/
031000      C      PLUSES
032000      DATA A(40),A(41),A(42),A(43)/3,X'3C',X'3C',X'FF'/
033000      C      SOLID
034000      DATA A(44),A(45)/1,X'FF'/
035000      C      BROAD CROSS HATCH
036000      DATA A(46),A(47),A(48),A(49)/3,X'92',X'92',X'FF'/
037000      C      THICK CROSS HATCH
038000      DATA A(50)/4/
039000      DATA A(51),A(52),A(53),A(54)/X'FF',X'FF',X'DB',X'DB'/
040000      C      FINE CROSS HATCH
041000      DATA A(54),A(55),A(56)/2,X'92',X'FF'/
042000      C      ALTERNATING PIXELS
043000      DATA A(57),A(58),A(59)/2,X'55',X'AA'/
044000      DATA B(1),B(2),B(3),B(4)/1,0,1,X'FF'/
045000      DATA IS(1),IS(2),IS(3),IS(4),IS(5),IS(6)/1,10,13,18,23,28/
046000      DATA IS(7),IS(8),IS(9),IS(10),IS(11)/30,32,34,37,40/
047000      DATA IS(12),IS(13),IS(14),IS(15),IS(16)/44,46,50,54,57/
048000      CALL CLS
049000      ENCODE(MSG,100)
050000      100      FORMAT('PAINTT AND SETXYR TESTS')
051000      CALL SETXY(0,0)
052000      CALL LOCATE(0)
053000      CALL GPRINT(23,MSG)

```

Appendix D/ Sample Programs

```
054000      CALL WAIT
055000      C
056000      C      PAINT ON A BLACK BACKGROUND
057000      C
058000      DO 10 I=1,16
059000      CALL SETXY(0,40)
060000      CALL SETXYR(639,199)
061000      CALL LINEB(1,-1)
062000      CALL SETXYR(-300,-100)
063000      ITMP=IS(I)
064000      CALL PAINTT(A(ITMP),1,B)
065000      CALL WAIT
066000      CALL VIEW(0,40,639,239,0,0)
067000      CALL VIEW(0,0,639,239,-1,-1)
068000      10      CONTINUE
069000      C
070000      C      PAINT ON A WHITE BACKGROUND
071000      C
072000      DO 11 I=1,16
073000      IF(I.EQ.12) GOTO 11
074000      CALL VIEW(0,40,639,239,0,0)
075000      CALL VIEW(0,0,639,239,-1,-1)
076000      CALL SETXY(0,40)
077000      CALL SETXYR(639,199)
078000      CALL LINEBF(1)
079000      CALL SETXYR(-300,-100)
080000      ITMP=IS(I)
081000      CALL PAINTT(A(ITMP),0,B(3))
082000      CALL WAIT
083000      11      CONTINUE
084000      RETURN
085000      END
```

Model 4 Computer Graphics

```
00100 SUBROUTINE GPTST
00200 C
00300 C GET AND PUT TEST
00400 C
00500 LOGICAL A(1000),MSG(16)
00600 CALL CLS
00700 ENCODE(MSG,100)
00800 100 FORMAT('GET AND PUT TEST')
00900 CALL SETXY(0,0)
01000 CALL LOCATE(0)
01100 CALL GPRINT(16,MSG)
01200 CALL VIEW(0,30,639,239,0,0)
01300 CALL SETXY(100,100)
01400 CALL SETXYR(30,30)
01500 CALL LINEBF(1)
01600 CALL GET(A,1000)
01700 CALL CLS
01800 CALL WAIT
01900 CALL SETXY(100,100)
02000 CALL PUT(A,1)
02100 CALL WAIT
02200 CALL VIEW(0,0,639,239,0,-1)
02300 RETURN
02400 END
```

Appendix D/ Sample Programs

```

001000      SUBROUTINE PPTST
002000      C
003000      C      PSET AND POINT TEST
004000      C
005000      LOGICAL POINT,MSG(21)
006000      CALL CLS
007000      ENCODE(MSG,100)
008000      100    FORMAT('PSET AND POINT TEST')
009000      CALL SETXY(0,0)
010000      CALL LOCATE(0)
011000      CALL GPRINT(19,MSG)
012000      CALL WAIT
013000      CALL CLS
014000      C
015000      C      SET AND CHECK ALL PIXELS
016000      C
017000      DO 10 I=0,639
018000      DO 11 J=0,239
019000      CALL SETXY(I,J)
020000      CALL PSET(1)
021000      K=POINT(L)
022000      IF(K.EQ.0) GOTO 999
023000      11    CONTINUE
024000      10    CONTINUE
025000      C
026000      C      RESET AND CHECK ALL PIXELS
027000      C
028000      DO 12 I=0,639
029000      DO 13 J=0,239
030000      CALL SETXY(I,J)
031000      CALL PSET(0)
032000      K=POINT(L)
033000      IF (K.EQ.1) GOTO 999
034000      13    CONTINUE
035000      12    CONTINUE
036000      CALL CLS
037000      ENCODE(MSG,101)
038000      101    FORMAT('PSET AND POINT PASSED')
039000      CALL SETXY(0,0)
040000      CALL LOCATE(0)
041000      CALL GPRINT(21,MSG)
042000      GOTO 1000
043000      999    CALL CLS
044000      ENCODE(MSG,102)
045000      102    FORMAT('PSET AND POINT FAILED')
046000      CALL SETXY(0,0)
047000      CALL LOCATE(0)
048000      CALL GPRINT(21,MSG)
049000      1000   CALL WAIT
050000      RETURN
051000      END

```

Model 4 Computer Graphics

```

00100      SUBROUTINE PRETST
00200      C
00300      C      PRESET AND POINT TEST
00400      C
00500      LOGICAL POINT,MSG(23)
00600      CALL CLS
00700      ENCODE(MSG,100)
00800      100      FORMAT('PRESET AND POINT TEST')
00900      CALL SETXY(0,0)
01000      CALL LOCATE(0)
01100      CALL GPRINT(23,MSG)
01200      CALL WAIT
01300      CALL CLS
01400      C
01500      C      SET AND CHECK ALL PIXELS
01600      C
01700      DO 10 I=0,639
01800      DO 11 J=0,239
01900      CALL SETXY(I,J)
02000      CALL PRESET(1)
02100      K=POINT(L)
02200      IF(K.EQ.0) GOTO 999
02300      11      CONTINUE
02400      10      CONTINUE
02500      C
02600      C      RESET AND CHECK ALL PIXELS
02700      C
02800      DO 12 I=0,639
02900      DO 13 J=0,239
03000      CALL SETXY(I,J)
03100      CALL PRESET(0)
03200      K=POINT(L)
03300      IF (K.EQ.1) GOTO 999
03400      13      CONTINUE
03500      12      CONTINUE
03600      CALL CLS
03700      ENCODE(MSG,101)
03800      101      FORMAT('PRESET AND POINT PASSED')
03900      CALL SETXY(0,0)
04000      CALL LOCATE(0)
04100      CALL GPRINT(23,MSG)
04200      GOTO 1000
04300      999      CALL CLS
04400      ENCODE(MSG,102)
04500      102      FORMAT('PRESET AND POINT FAILED')
04600      CALL SETXY(0,0)
04700      CALL LOCATE(0)
04800      CALL GPRINT(23,MSG)
04900      1000      CALL WAIT
05000      RETURN
05100      END

```

Appendix D/ Sample Programs

```
00100 SUBROUTINE SCRTST
00200 C
00300 C SCREEN TEST
00400 C
00500 LOGICAL MSG(11)
00600 CALL CLS
00700 ENCODE(MSG,100)
00800 100 FORMAT('SCREEN TEST')
00900 CALL SETXY(0,0)
01000 CALL LOCATE(0)
01100 CALL GPRINT(11,MSG)
01200 CALL WAIT
01300 CALL SETXY(300,120)
01400 CALL CIRCLE(100,1,0.0,6.28,0.5)
01500 CALL CIRCLE(100,1,0.0,6.28,0.25)
01600 CALL CIRCLE(50,1,0.0,6.28,0.5)
01700 CALL PAINT(1,1)
01800 C
01900 C GRAPHICS SCREEN
02000 C
02100 CALL SCREEN(0)
02200 CALL WAIT
02300 CALL WAIT
02400 CALL WAIT
02500 C
02600 C TEXT SCREEN
02700 C
02800 CALL SCREEN(1)
02900 CALL WAIT
03000 CALL WAIT
03100 CALL WAIT
03200 C
03300 C GRAPHICS SCREEN
03400 C
03500 CALL SCREEN(0)
03600 CALL WAIT
03700 CALL WAIT
03800 CALL WAIT
03900 RETURN
04000 END
```

Model 4 Computer Graphics

```
001000      SUBROUTINE VTEST
002000      C
003000      C      VIEW AND FVIEW TEST
004000      C
005000      INTEGER FVIEW
006000      LOGICAL MSG(19)
007000      CALL CLS
008000      ENCODE(MSG,1000)
009000      1000  FORMAT('VIEW AND FVIEW TEST')
010000      CALL SETXY(0,0)
011000      CALL LOCATE(0)
012000      CALL GPRINT(19,MSG)
013000      CALL WAIT
014000      C
015000      C      DRAW VIEWPORT AND CIRCLES
016000      C
017000      CALL VIEW(0,40,639,239,0,1)
018000      CALL DCIRCL(1)
019000      C
020000      C      DRAW VIEWPORT AND LINES
021000      C
022000      CALL VIEW(20,50,619,229,1,0)
023000      CALL DLINE(0)
024000      C
025000      C      DRAW VIEWPORT AND CIRCLES
026000      C
027000      CALL VIEW(40,60,599,209,0,0)
028000      CALL DCIRCL(1)
029000      C
030000      C      DRAW VIEWPORT AND LINES
031000      C
032000      CALL VIEW(60,70,579,199,1,1)
033000      CALL DLINE(0)
034000      C
035000      C      CLEAR SCREEN
036000      C
037000      IX1=FVIEW(0)
038000      IY1=FVIEW(1)
039000      IX2=FVIEW(2)
040000      IY2=FVIEW(3)
041000      CALL VIEW(60-IX1,70-IY1,60+IX2,40+IY2,0,1)
042000      CALL CLS
043000      RETURN
044000      END
```

Appendix D/ Sample Programs

```
04500      SUBROUTINE DCIRCL(ICLR)
04600      CALL SETXY(100,100)
04700      DO 10 I=5,300,5
04800      CALL CIRCLE(I,ICLR,0.0,6.28,0.5)
04900 10      CONTINUE
05000      CALL WAIT
05100      RETURN
05200      END
```

```
05300      SUBROUTINE DLINE(ICLR)
05400      DO 11 I=2,200,4
05500      CALL SETXY(-10,-10)
05600      CALL SETXY(I+200,I)
05700      CALL LINE(ICLR,-1)
05800 11      CONTINUE
05900      CALL WAIT
06000      RETURN
06100      END
```

Model 4 Computer Graphics

```
00100      SUBROUTINE WAIT
00200      C
00300      C      THIS SUBROUTINE INTRODUCES A TIME DELAY
00400      C
00500      DO 11 J=1,20
00600      DO 10 I=1,100000
00700      10      CONTINUE
00800      11      CONTINUE
00900      RETURN
01000      END
```


Appendix E/ Base Conversion Chart

Appendix E/ Base Conversion Chart

DEC.	HEX.	BINARY	DEC.	HEX.	BINARY
0	00	00000000	40	28	00101000
1	01	00000001	41	29	00101001
2	02	00000010	42	2A	00101010
3	03	00000011	43	2B	00101011
4	04	00000100	44	2C	00101100
5	05	00000101	45	2D	00101101
6	06	00000110	46	2E	00101110
7	07	00000111	47	2F	00101111
8	08	00001000	48	30	00110000
9	09	00001001	49	31	00110001
10	0A	00001010	50	32	00110010
11	0B	00001011	51	33	00110011
12	0C	00001100	52	34	00110100
13	0D	00001101	53	35	00110101
14	0E	00001110	54	36	00110110
15	0F	00001111	55	37	00110111
16	10	00010000	56	38	00111000
17	11	00010001	57	39	00111001
18	12	00010010	58	3A	00111010
19	13	00010011	59	3B	00111011
20	14	00010100	60	3C	00111100
21	15	00010101	61	3D	00111101
22	16	00010110	62	3E	00111110
23	17	00010111	63	3F	00111111
24	18	00011000	64	40	01000000
25	19	00011001	65	41	01000001
26	1A	00011010	66	42	01000010
27	1B	00011011	67	43	01000011
28	1C	00011100	68	44	01000100
29	1D	00011101	69	45	01000101
30	1E	00011110	70	46	01000110
31	1F	00011111	71	47	01000111
32	20	00100000	72	48	01001000
33	21	00100001	73	49	01001001
34	22	00100010	74	4A	01001010
35	23	00100011	75	4B	01001011
36	24	00100100	76	4C	01001100
37	25	00100101	77	4D	01001101
38	26	00100110	78	4E	01001110
39	27	00100111	79	4F	01001111

Model 4 Computer Graphics

DEC.	HEX.	BINARY	DEC.	HEX.	BINARY
80	50	01010000	120	78	01111000
81	51	01010001	121	79	01111001
82	52	01010010	122	7A	01111010
83	53	01010011	123	7B	01111011
84	54	01010100	124	7C	01111100
85	55	01010101	125	7D	01111101
86	56	01010110	126	7E	01111110
87	57	01010111	127	7F	01111111
88	58	01011000	128	80	10000000
89	59	01011001	129	81	10000001
90	5A	01011010	130	82	10000010
91	5B	01011011	131	83	10000011
92	5C	01011100	132	84	10000100
93	5D	01011101	133	85	10000101
94	5E	01011110	134	86	10000110
95	5F	01011111	135	87	10000111
96	60	01100000	136	88	10001000
97	61	01100001	137	89	10001001
98	62	01100010	138	8A	10001010
99	63	01100011	139	8B	10001011
100	64	01100100	140	8C	10001100
101	65	01100101	141	8D	10001101
102	66	01100110	142	8E	10001110
103	67	01100111	143	8F	10001111
104	68	01101000	144	90	10010000
105	69	01101001	145	91	10010001
106	6A	01101010	146	92	10010010
107	6B	01101011	147	93	10010011
108	6C	01101100	148	94	10010100
109	6D	01101101	149	95	10010101
110	6E	01101110	150	96	10010110
111	6F	01101111	151	97	10010111
112	70	01110000	152	98	10011000
113	71	01110001	153	99	10011001
114	72	01110010	154	9A	10011010
115	73	01110011	155	9B	10011011
116	74	01110100	156	9C	10011100
117	75	01110101	157	9D	10011101
118	76	01110110	158	9E	10011110
119	77	01110111	159	9F	10011111

Appendix E/ Base Conversion Chart

DEC.	HEX.	BINARY	DEC.	HEX.	BINARY
160	A0	101000000	200	C8	11001000
161	A1	101000001	201	C9	11001001
162	A2	101000010	202	CA	11001010
163	A3	101000011	203	CB	11001011
164	A4	101000100	204	CC	11001100
165	A5	101000101	205	CD	11001101
166	A6	101000110	206	CE	11001110
167	A7	101000111	207	CF	11001111
168	A8	10101000	208	D0	11010000
169	A9	10101001	209	D1	11010001
170	AA	10101010	210	D2	11010010
171	AB	10101011	211	D3	11010011
172	AC	10101100	212	D4	11010100
173	AD	10101101	213	D5	11010101
174	AE	10101110	214	D6	11010110
175	AF	10101111	215	D7	11010111
176	B0	10110000	216	D8	11011000
177	B1	10110001	217	D9	11011001
178	B2	10110010	218	DA	11011010
179	B3	10110011	219	DB	11011011
180	B4	10110100	220	DC	11011100
181	B5	10110101	221	DD	11011101
182	B6	10110110	222	DE	11011110
183	B7	10110111	223	DF	11011111
184	B8	10111000	224	E0	11100000
185	B9	10111001	225	E1	11100001
186	BA	10111010	226	E2	11100010
187	BB	10111011	227	E3	11100011
188	BC	10111100	228	E4	11100100
189	BD	10111101	229	E5	11100101
190	BE	10111110	230	E6	11100110
191	BF	10111111	231	E7	11100111
192	C0	11000000	232	E8	11101000
193	C1	11000001	233	E9	11101001
194	C2	11000010	234	EA	11101010
195	C3	11000011	235	EB	11101011
196	C4	11000100	236	EC	11101100
197	C5	11000101	237	ED	11101101
198	C6	11000110	238	EE	11101110
199	C7	11000111	239	EF	11101111

Model 4 Computer Graphics

DEC.	HEX.	BINARY

240	F0	11110000
241	F1	11110001
242	F2	11110010
243	F3	11110011
244	F4	11110100
245	F5	11110101
246	F6	11110110
247	F7	11110111
248	F8	11111000
249	F9	11111001
250	FA	11111010
251	FB	11111011
252	FC	11111100
253	FD	11111101
254	FE	11111110
255	FF	11111111

Appendix F/ Pixel Grid Reference

The following hexadecimal numbers include commonly used tiling designs.

Important Note: You cannot use more than two empty rows of tiles when tiling or you'll get an Illegal Function Call error.

Example (four rows of empty tiles):

`CHR$(&HFF)+CHR$(&HFF)+CHR$(&H00)+CHR$(&H00)+CHR$(&H00)+CHR$(&H00)`

gives you an Illegal Function Call error.

1. "X"

`CHR$(&H41)+CHR$(&H22)+CHR$(&H14)+CHR$(&H08)+CHR$(&H14)
+CHR$(&H22)+CHR$(&H41)+CHR$(&H00)`

									Hex	Decimal
	0	1	0	0	0	0	0	1	41	65
	0	0	1	0	0	0	1	0	22	34
	0	0	0	1	0	1	0	0	14	20
	0	0	0	0	1	0	0	0	08	8
	0	0	0	1	0	1	0	0	14	20
	0	0	1	0	0	0	1	0	22	34
	0	1	0	0	0	0	0	1	41	65
	0	0	0	0	0	0	0	0	00	0

2. "Fine" horizontal lines

`CHR$(&HFF)+CHR$(&H00)`

									Hex	Decimal
	1	1	1	1	1	1	1	1	FF	255
	0	0	0	0	0	0	0	0	00	0

Model 4 Computer Graphics

3. "Medium" horizontal lines

CHR\$(&HFF)+CHR\$(&HFF)+CHR\$(&H00)+CHR\$(&H00)

1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1
0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0

Hex	Decimal
FF	255
FF	255
00	0
00	0

4. Diagonal lines

(Right to left)

CHR\$(&H03)+CHR\$(&H0C)+CHR\$(&H30)+CHR\$(&HC0)

0	0	0	0	0	0	1	1
0	0	0	0	1	1	0	0
0	0	1	1	0	0	0	0
1	1	0	0	0	0	0	0

Hex	Decimal
03	3
0C	12
30	48
C0	192

(Left to right)

CHR\$(&HC0)+CHR\$(&H30)+CHR\$(&H0C)+CHR\$(&H03)

1	1	0	0	0	0	0	0
0	0	1	1	0	0	0	0
0	0	0	0	1	1	0	0
0	0	0	0	0	0	1	1

Hex	Decimal
C0	192
30	48
0C	12
03	3

Appendix F/ Pixel Grid Reference

5. "Fine" vertical lines
CHR\$(&HAA)

1	Ø	1	Ø	1	Ø	1	Ø
---	---	---	---	---	---	---	---

Hex	Decimal
AA	170

6. "Medium" vertical lines
CHR\$(&HCC)

1	1	Ø	Ø	1	1	Ø	Ø
---	---	---	---	---	---	---	---

Hex	Decimal
CC	204

7. "Coarse" vertical lines
CHR\$(&HF0)

1	1	1	1	Ø	Ø	Ø	Ø
---	---	---	---	---	---	---	---

Hex	Decimal
F0	240

8. One-pixel dots
CHR\$(&H22) + CHR\$(&H00)

Ø	Ø	1	Ø	Ø	Ø	1	Ø
Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø

Hex	Decimal
22	34
00	0

9. Two-pixel dots
CHR\$(&H99) + CHR\$(&H66)

1	Ø	Ø	1	1	Ø	Ø	1
Ø	1	1	Ø	Ø	1	1	Ø

Hex	Decimal
99	153
66	102

Model 4 Computer Graphics

10. Pluses ('+')

CHR\$(&H3C)+CHR\$(&H3C)+CHR\$(&HFF)

Ø	Ø	1	1	1	1	Ø	Ø
Ø	Ø	1	1	1	1	Ø	Ø
1	1	1	1	1	1	1	1

Hex	Decimal
3C	60
3C	60
FF	255

11. Solid (all pixels ON)

CHR\$(&HFF)

1	1	1	1	1	1	1	1
---	---	---	---	---	---	---	---

Hex	Decimal
FF	255

12. "Broad" cross-hatch

CHR\$(&H92)+CHR\$(&H92)+CHR\$(&HFF)

1	Ø	Ø	1	Ø	Ø	1	Ø
1	Ø	Ø	1	Ø	Ø	1	Ø
1	1	1	1	1	1	1	1

Hex	Decimal
92	146
92	146
FF	255

13. "Thick" cross-hatch

CHR\$(&HFF)+CHR\$(&HFF)+CHR\$(&HDB)+CHR\$(&HDB)

1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1
1	1	Ø	1	1	Ø	1	1
1	1	Ø	1	1	Ø	1	1

Hex	Decimal
FF	255
FF	255
DB	219
DB	219

Appendix F/ Pixel Grid Reference

14. "Fine" cross-hatch

CHR\$(&H92)+CHR\$(&HFF)

1	Ø	Ø	1	Ø	Ø	1	Ø
1	1	1	1	1	1	1	1

Hex	Decimal
92	146
FF	255

15. Alternating pixels

CHR\$(&H55)+CHR\$(&HAA)

Ø	1	Ø	1	Ø	1	Ø	1
1	Ø	1	Ø	1	Ø	1	Ø

Hex	Decimal
55	85
AA	170

Appendix F/ Line Style Reference

Type	Binary Numbers	Hex	Decimal
Long dash	0000 0000 1111 1111	&H00FF	255
Short dash	1111 0000 1111 0000	&HF0F0	-3856
"Short-short" dash	1100 1100 1100 1100	&HCCCC	-13108
Solid line	1111 1111 1111 1111	&HFFFF	-1
OFF/ON	0101 0101 0101 0101	&H5555	21845
"Wide" dots	0000 1000 0000 1000	&H0808	2056
"Medium" dots	1000 1000 1000 1000	&H8888	-30584
"Dot-dash"	1000 1111 1111 1000	&H8FF8	-28680

Index

- absolute coordinates 40-42, 83
- AND 34, 35, 80, 87
- arc 13, 18
- array 19-21, 34, 35, 40, 72-74, 80, 89-90
- array limits 20, 73, 74
- array name 19, 20, 34, 87, 88
- aspect ratio 13, 14, 17, 72
- BASIC 5, 11, 19, 34-35, 70
- BASICG 7, 11, 12, 28, 33, 34, 35, 69, 97, 103
- BASICG command 11, 13
- BASICG error messages 89-93
- BASICG functions 12, 13
- binary numbers 24, 27-29, 129
- Cartesian system 8, 12, 40, 82, 83
- CIRCLE 11, 13-19, 71, 72, 87, 95
- CLR 11, 87
- CLS 71, 87, 95
- communication drivers 45
- current coordinates 69, 70, 72-73, 82
- DEBUG 45
- DO 73-74, 81, 83
- double-precision 12
- ellipse 5, 17-19, 71, 87
- FORMS 47, 103
- FORTRAN 5, 45, 69-71, 75, 104, 105
- free memory 11, 28, 70
- FVIEW 71, 84, 95
- GCLS 45, 48, 87
- GET 11, 19-21, 35, 40, 71, 72-73, 95
- GLOAD 45, 46, 49, 87-88
- GLOCATE 11, 21, 22, 32, 87-88
- GPRINT 45, 47, 71, 74, 75, 88, 95
- GPRT 2 45, 48, 88
- GPRT 3 45, 47-48, 88
- graphics board 85, 86
- GRAPHICS ERROR 70, 75
- graphics memory 45-47, 48, 49, 103-104
- graphics utilities 45-49
- GROFF 45, 48, 88
- GRON 45, 49, 88
- GRPINI 71, 75, 95
- GRPLIB/REL 69, 70
- GSAVE 45, 49, 88
- hard disk 4
- hex numbers 23, 24, 28-29, 123, 129
- initialization 69-70
- integer 13-14, 19, 20, 73
- INTEGER 72, 73, 74, 76, 82-83
- integer range 8, 15, 23, 24, 75-76, 89
- I/O port mapping 85
- LINE 11, 23-25, 69, 71, 88, 95
- LINE-CMD 69, 75
- line styles 23, 24, 129
- LINEB 69, 71, 76-77, 95
- LINEB-CMB 69
- LINEBF 69, 71, 76-77, 95
- LINEBF-CMD 69
- loading BASICG 11, 12
- LOCATE 71, 95
- LOGICAL 72-81, 82-84
- notational conventions 5
- numeric expressions 15, 26
- numeric values 13
- options programming 86
- OR 34, 35, 80-81, 87
- PAINT 11, 25-30, 40, 69, 71, 78, 88, 95
- PAINT-CMD 69
- PAINTT 69, 71, 78-79, 95
- PAINTT-CMD 69
- pie-slice 13
- pixel 7, 8, 23-24, 26, 27, 30-34, 35, 71, 73, 79, 80, 84, 85, 123
- pixel area 19-20, 35, 38, 39, 72-73, 80-81, 88
- POINT 12, 30, 31, 71, 84, 88, 96
- PRESET 11, 32, 33, 34, 35, 71, 79, 80-81, 87, 88, 96
- previous coordinates 69, 70, 72-73, 82
- PRINT #-3 11, 33, 88
- printers 5
- PSET 11, 33-35, 38, 71, 80, 87, 88, 96
- PUT 11, 19-20, 34-36, 38, 39, 71, 80-81, 88
- real 20, 73
- REAL 72
- relative origin 40, 82-83
- resolution 7
- SCREEN 11, 39, 71, 81, 88, 96
- SCREEN-CMD 12, 81
- screen dump 47
- SETXY 69, 70, 71, 73, 76, 82, 96
- SETXYR 69, 70, 71, 75-76, 82, 96
- single-precision 12-13, 17-18, 87
- starting-up 12
- strings 26-28
- subrouting library 7, 69, 70, 83, 95
- text screen 8, 11, 13, 39, 81, 85, 87
- video display 8, 85
- VIEW 11, 40-42, 71, 82-83, 88, 96
- VIEW (command) 11, 40-42
- VIEW (function) 12, 43-44, 82, 83, 88
- viewport 11, 12, 40-44, 71, 82-83, 84, 88

RADIO SHACK, A DIVISION OF TANDY CORPORATION

U.S.A.: FORT WORTH, TEXAS 76102
CANADA: BARRIE, ONTARIO L4M 4W5

TANDY CORPORATION

AUSTRALIA	BELGIUM	U. K.
91 KURRAJONG ROAD MOUNT DRUITT, N.S.W. 2770	PARC INDUSTRIEL DE NANINNE 5140 NANINNE	BILSTON ROAD WEDNESBURY WEST MIDLANDS WS10 7JN