

7134


Notes: 1. 40 pin DIP socket to be used for FD1771B-01.
No sockets for XTAL or other ICs except
RAMs on other schematic sheet.

2. 0.01 μ F Disc capacitors for rail
by-pass distributed as PCB layout
allows.

3. 650 mA @ 5 volts r/g'd this sheet.
20 mA @ 12 volts r/g'd this sheet.
0.5 μ A @ 5 volts r/g'd this sheet.

* LOCATE NEAR IC FOR PROPER OPERATION

4. N.C. = NOT CONNECTED

5.  INDICATES PAD ON SCSI PRINTER
INTERFACE

For further information
call 390-3596

Robt. Kubala
Steve Leiwinger

INTERFACE BOX for TFS-80
Printer, Floppy Disk, &
Heart Beat.

This schematic does not
show memory expansion
or cassette switch circuits
also on this P.C.B.

REV D 3-15-78 M. HOWARD

Drawn - Weds. 30 MAR. 77
Rev A 12/6/77 CLK
REV B 1/20/78 SWW
Rev C 1/21/78 CLK 1 OF 5


APR. 24 1978


**Check
Print**

26-1140

Pharmaceutical

ROM 1





Print Check

REV 1 2 8 1 1978

COMPONENT SIDE SHOWN

3 of 3

26-1140